

FLORIDA PUBLIC SERVICE COMMISSION

DIVISION OF APPEALS

DOCKET NO. 010105-GU

RULE NO:

RULE TITLE:

25-7.063

METER ACCURACY AT INSTALLATION

NOTICE OF CHANGE

Notice is hereby given that the following changes have been made to the proposed rule in accordance with subparagraph 120.54(3)(d)1., F.S., published in Volume 27, No. 9, March 2, 2001, of the Florida Administrative Weekly:

25-7.063 Meter Accuracy at Installation.

(1) A new gas meter shall be within plus or minus 1 percent of accuracy to be installed for customer use. Manufacturers' test data may be used if there is no indication of damage to the meters resulting from the shipping process. If damage is apparent, in order for the manufacturers' test data to be used, a representative sample of not less than 10 percent of the meters in the damaged shipping unit, such as a pallet or container, shipment shall be tested and found to be within accuracy limits. If any meter of the sample is found not to be within accuracy limits, the entire shipping unit shipment must be tested, and where necessary, the meters adjusted to within the plus or minus 1 percent accuracy limits.

(2) Every meter removed from service when opened for repair

APP  
CAF  
CMP  
COM  
CPR  
COR  
LCO  
CPC  
PAI  
RCO  
SEC  
SER  
OTH

DOCUMENT NUMBER-DATE

05836 MAY-95

FPSC-RECORDS/REPORTING

RECEIVED  
MAY - 9 4 11: 24  
DEPARTMENT OF STATE  
TALLAHASSEE, FLORIDA

shall be adjusted to be not more than 1 percent fast or 1 percent slow before being reset. If not opened for repairs, the meter may be reset without adjustment if found to be not more than 1 percent fast or not more than 1 percent slow provided the meter is otherwise in good condition.

(3) No meter may be installed unless it has been tested within the previous 12 months and found to be within the accuracy limits established by this rule.

Specific Authority: 366.05(1), F.S.

Law Implemented: 366.05(1), F.S.

History-Repromulgated 1/8/75, 5/4/75, Amended 2/13/84, formerly 25-7.63,\_\_\_\_\_.