

KWRU 014754

**Cherrington Enterprises, Inc.**  
Cherrington Beachcleaners

PO Box V  
Cherrington Beachcleaners  
beach@cherrington.net  
Fairfax, MN 55332

Phone: 507-426-7261 Fax: 507-426-7263  
Tollfree 1-800-966-1588



**Fax**

To: Doug Carter From: Judi Nelson

Fax: 305-294-1212 Date: March 31, 2006

Phone: 305-522-3600 Pages: 5 with cover

Re: Cherrington 3000 cc:

Urgent  For Review  Please Comment  Please Reply  Please Recycle

Comments:

Doug,

Here is the proposal which we discussed for the Cherrington 3000 Sandstifer. It is as we discussed yesterday, with the exception that we need to run it for the calendar year (9 months remaining) rather than a full twelve month period.

I'll look forward to talking to you on Monday to see what you've decided.

Thanks, and have a great weekend!

Judi  
Carter

~~Chris~~

Chris,

learn is over in 9 months

should we not for

12 months or will we

know in 9 months is

this is what we want

Doug

KWRU 014755



Keys Environmental  
6630 Front Street  
Key West, FL 33040

**QUOTATION**

This quote is valid through April 5, 2006.  
Prices do not include State or County Sales or Use Tax.  
Prices are in U.S. Dollars.

Inquiry No: 230247  
Date: March 31, 2006  
Terms: 10% Down, Balance Due on Shipment  
FOB: Factory  
Shipment: 30 Days or Less ARO

Qty	Part No.	Description	Price	Amount
1		Cherrington Model 3000 Beachcleaner / Sandstriker	\$42,300.00	

With the Following Features:

- Self propelled, zero turn, hydrostatic drive
- Diesel engine (24 HP, liquid cooled)
- Cleaning method - Slanted sifting screens / overhead flights
- Hydraulic rollover hopper with maximum 5' 6" dump height and 9 cu. ft. / 1000 lbs capacity
- Cleaning width - 48" with digger extension option, 36" without
- Cleaning speed - 1 to 5 MPH
- Digging depth adjustable between 0 to 4 inches in varying applications
- Corrosion and abrasion resistant coating - Crit blasted oven baked primer & polyester finish
- Hot dip galvanized screen frames, flights, and other components
- Certified R.O.P.S. / rollover protection
- Automatic parking brake
- Groomer to smooth and aerate
- Interchangeable screens

**FREIGHT**  
TOTAL, FOB Key West, FL

\$2,000.00  
~~\$44,300.00~~

Cherrington Beachcleaners Demonstrator Model 3000  
FOB Key West, FL  
Offered as long as available

**LEASE PROPOSAL Cherrington Beachcleaners Demonstrator Model 3000**

Lease of unit for period of 9 months, from April 1, 2006 through December 31, 2006. Lessee to furnish certificate of insurance. Hours over term of lease not to exceed 200 for the period, or 25 per individual month. Normal warranty to apply. Lessee responsible for regular maintenance of unit and purchase of any wear parts. Two options:  
 > In advance, one payment of \$9,000.00, plus applicable sales tax  
 > In advance, payment of \$2,000.00. Monthly payment of \$1,000.00, due first of each month commencing April 1, 2006 through December 1, 2006. Plus applicable sales tax.  
 100% of payment to apply to purchase price of \$33,900.00, which must occur by December 31, 2006.

Attached Specifications are a part of this quote.

Accepted By \_\_\_\_\_ Date \_\_\_\_\_

Cherrington Enterprises reserves the right to change specifications without notice and without incurring obligation.  
 Not responsible for shipping delays beyond our control.  
 Cherrington Enterprises / PO Box V / Fairfax, MN 55332-0901 / Phone: 800-966-1588 / Fax: 507-426-7263  
 E-mail: beachcleaners@cherrington.net / Website: www.cherrington.net

**Specifications for Cherrington Model 3000 Beachcleaner / Sandstriker**

Length (overall)	111"
Height	84"
Weight	3400 lbs
Width (overall)	59"
Wheel Base C-C	78"
Wheel Span C-C	42"
Turning Radius	Pivots on either rear wheel
Cleaning Width	36"
With Optional Digger Extensions	48"
Digging Depth	0" - 4" in varying applications
Ground Clearance	5"
Hopper Capacity	9 cu. ft / 1000 lbs.
Dump Height	5'6"
Groomer; automatic or independent control	60"
Engine Type	24 HP Liquid Cooled Diesel
Propulsion	All wheel hydrostatic drive
Secondary Systems	Hydraulic (Controlled from operator's position)
Steering	Prioritized power
Cleaning Method	Slanted sifting screens & overhead flights
Speed	0 - 5 MPH
Tires	29 x 12.50-15 NHS STG
Digger Points	High carbon steel
Paint	Grit blasted, corrosion & abrasion resistant oven baked primer & polyester top coat or equivalent
Color	Industrial yellow
Interchangeable screens	Abrasion & corrosion resistant Corten steel OR oil tempered hardened woven wire

**Engine:** The machine is furnished with a diesel engine producing approximately 24 horsepower. The engine is of adequate size to propel the machine with all power accessories in operation.

**Drive System:** A closed loop hydrostatic drive transmits variable speed forward and reverse power to all wheels. A separate fixed displacement pump provides power to the hopper, hoist, dump, and digger-depth control cylinders, the screen oscillator motor, and the overhead conveyor motor.

**Wheels and Tires:** The machine has one front and two rear wheels. Steering is on the front wheel for best maneuverability. All tires are of a minimum size 29 x 12.50-15 NHS high flotation, with a super terra-grip tread. Rear tires are fluid filled for added traction and a lower center of gravity.

**Oscillating Screen and Digger:** The machine is capable of digging a loose dry sand depth of 4 inches, fully controlled hydraulically by the operator while the machine is in motion. The digger points are of high carbon steel. The minimum cleaning width is 36 inches. The easily changed oscillating screens come with four different size openings. A T-bar overhead flight system bolted to two heavy duty steel (620 implement) chains is used to move debris collected on the screens into the hopper.

**Hopper:** The hopper has a capacity of one-third cubic yard. It is hydraulically operated for dumping with a five foot six inch clearance in the raised position, capable of dumping into debris boxes or pick-up trucks. The dumping operation is fully controlled from the operator's normal seated position.

### Specifications for Cherrington Model 3000 Beachcleaner / Sandblifter

**Paint:** All exterior metal surfaces are grit blasted, epoxy primed and topcoated with chemical, corrosion, and abrasion resistant oven baked primer & polyester top coat or equivalent. Standard color is Industrial yellow. Screen frame components, lights and groomer components are hot dip galvanized.

**Operator Controls:** All controls are actuated from the operator's station.

**Safety Features:** The machine has the following safety features included on the machine in accordance with current standards:

1. Safety guards and shielding
2. Slow moving vehicle symbol
3. Neutral start switch
4. Flashing beacon
5. Emergency stop switch built into the footrest
6. Certified R.O.P.S.

#### Other Features:

1. Engine hourmeter
2. Fuel level indicator
3. Engine temperature gauge
4. Engine oil pressure gauge
5. Voltmeter gauge
6. Locking caps on fuel and hydraulic fluid tanks
7. Towing lockout which enables the machine to be towed short distances in the event of engine failure
8. Switches to prevent hoist and hopper damage

**Optional Equipment and Spare Parts Packages:** See page one.

**Manufacturer's Identification:** A durable identification plate stating the manufacturer's name, location, model, and other suitable information to identify the Beachcleaner for parts or repair is permanently attached to the frame.

**Materials:** All materials, parts and assemblies are new and are of current manufacture. Workmanship, fabrication and assembly are in conformance with standard manufacturing and engineering practices. Bolts are of sufficient length to assure a full thread nut. All bolts are fitted with self-locking nuts or with lock washers. All welds and welding practices conform to the latest American Welding Society Standards.

**Warranty:** 12 months on machine, including engine, pumps, motors and other components. Excludes normal maintenance and replacement wear parts, such as, but not limited to, electrical components, filters, oil, belts, chains, conveyor parts, digger points and screens.

**Disclaimer:** The Company reserves the right to make any changes deemed necessary to the above specifications without notice, and is not liable for unintentional errors in the specifications.