Amount \$42,300.00



Keys Environmental 6630 Front Street Key West, FL 33040 Inquiry No:

230247

Date:

March 31, 2006

Terms:

10% Down, Balance Due on Shipment

FOB: Factory

Shipment:

30 Days or Less ARO

## QUOTATION

This quote is valid through April 5, 2006. Prices do not include State or County Sales or Use Tax. Prices are in U.S. Dollars.

Oty	Part No.	Description	_
		Cherrington Model 3000 Beachcleaner / Sandsifter	Price
		With the Following Features:	\$4
		Self propelled, zero turn, hydrostatic drive	
		Diesel engine (24 HP, liquid cooled)	
		Cleaning method — Slanted sifting screens / overhead flights	
		Hydraulic rollover hopper with maximum 5° 6" dump height and 9 cu. ft. / 10 Cleaning width – 48" with digger extension option, 36" without Cleaning speed – I to 5 MPH	00 lbs capacity
		Digging death adjustable between 0 to 4 inch.	
		Digging depth adjustable between 0 to 4 inches in varying applications Corrosion and abrasion resistant coating — Grit blasted oven baked primer & p Hot dip galvanized screen frames, flights, and other components	oolyester finish
		Certified R.O.P.S. / rollover protection	
		Automatic parking brake	
		Groomer to smooth and aerate	
		Interchangeable screens	
		FREIGHT	m m
		TOTAL, FOB Key West, FL.	<u>\$2</u>

<u>\$2,000.00</u> \$44,300,00

Cherrington Beachcleaners Demonstrator Model 3000

FOB Key West, FL

Offered as long as available

\$33,900.00

### LEASE PROPOSAL Cherrington Beachcleaners Demonstrator Model 3000

Lease of unit for period of 9 months, from April 1, 2006 through December 31, 2006. Lessee to furnish certificate of insurance. Hours over term of lease not to exceed 200 for the period, or 25 per individual month. Normal warranty to apply. Lessee responsible for regular maintenance of unit and purchase of any wear parts.

In advance, one payment of \$9,000.00, plus applicable sales tax

In advance, payment of \$2,000.00. Monthly payment of \$1,000.00, due first of each month commencing April 1, 2006 through December 1, 2006. Plus applicable sales tax.

100% of payment to apply to purchase price of \$33,900.00, which must occur by December 31, 2006.

Attached Specifications are a part of this quote.			
by: Qualification	Accepted By	Date	

Cherrington Enterprises reserves the right to change specifications without notice and without incurring obligation. Not responsible for shipping delays beyond our control. Cherrington Enterprises / PO Box V / Fairfax, MN 55332-0901 / Phone: 800-966-1588 / Fax: 507-426-7263

E-mail: benches@cherrington.net / Website: www.cherrington.net

PAGE 03

03

PAGE

#### Page 2

# Specifications for Cherrington Model 3000 Beachcleaner / Sandsifter

Potigri (Actail)	
Height	
Weight	
Width (overall)	3400 lbs
Wheel Base C-C	59°°
TO THE RESIDENCE OF THE PROPERTY OF THE PROPER	4
Turning Radius	42"Pivots on either rear wheel
Cleaning Width	Pivots on either rear wheel36"
With Optional Digger Extensions	
Digging Depth	48"
Ground Clearance	
TOTAL COMPONENTS SERVICES SERV	D 01.000.01
THE THE PARTY OF T	- + - + +
Groomer; automatic or independent control	5'6"
Engine Type	60"
Propulsion .	24 HP Liquid Cooled Diesel
Secondary Systems	All wheel hydrostatic drive
Steering	riydraulic (Controlled from operator's position)
Cleaning Method	Prioritized power
Speed	Slanted sifting screens & overhead flights
Tires	0 – 5 MPH
THE THE PROPERTY OF THE PROPER	STOME ATTOM balead maintain B
Color	stant oven baken primer & polyester top coat or equivalent
Interchangeable screens Abrasion & corrosion re	sistant Corten steel OR oil tempered hardened woven wire
Dump Height Groomer; automatic or independent control Engine Type Propulsion Secondary Systems Steering Cleaning Method Speed Tires Digger Points Paint Grit blasted, corrosion & abrasion resicular	9 cu. ft / 1000 lbs 5'6' 60' 24 HP Liquid Cooled Diese All wheel hydrostatic drive Prioritized power Slanted sifting screens & overhead flights 0 - 5 MPH 29 x 12.50-15 NHS STG High carbon steel

Engine: The machine is furnished with a diesel engine producing approximately 24 horsepower. The engine is of adequate size to propel the machine with all power accessories in operation.

<u>Drive System:</u> A closed loop hydrostatic drive transmits variable speed forward and reverse power to all wheels. A separate fixed displacement pump provides power to the hopper, hoist, dump, and digger-depth control cylinders, the screen oscillator motor, and the overhead conveyor motor.

Wheels and Tires: The machine has one front and two rear wheels. Steering is on the front wheel for best maneuverability. All tires are of a minimum size 29 x 12.50-15 NHS high flotation, with a super terra-grip tread. Rear tires are fluid filled for added traction and a lower center of gravity.

Oscillating Screen and Digger: The machine is capable of digging a loose dry sand depth of 4 inches, fully controlled hydraulically by the operator while the machine is in motion. The digger points are of high carbon steel. The minimum cleaning width is 36 inches. The easily changed oscillating screens come with four different size openings. A T-bar overhead flight system bolted to two heavy duty steel (620 implement) chains is used to move debris collected on the screens into the hopper.

<u>Hopper:</u> The hopper has a capacity of one-third cubic yard. It is hydraulically operated for dumping with a five foot six inch clearance in the raised position, capable of dumping into debris boxes or pick-up trucks. The dumping operation is fully controlled from the operator's normal seated position.

PAGE 04

Page 3

### Specifications for Cherrington Model 3000 Beachcleaner / Sandsifter

Paint: All exterior metal surfaces are grit blasted, epoxy primed and topcoated with chemical, corrosion, and abrasion resistant oven baked primer & polyester top coat or equivalent. Standard color is Industrial yellow. Screen frame components, flights and groomer components are hot dip galvanized.

Operator Controls: All controls are actuated from the operator's station.

Safety Features: The machine has the following safety features included on the machine in accordance with current standards.

- 1. Safety guards and shielding
- Slow moving vehicle symbol
- Neutral start switch
- Flashing beacon
- Emergency stop switch built into the footrest
- Certified R.O.P.S.

## Other Features:

- 1. Engine hourmeter
- 2. Fuel level indicator
- Engine temperature gauge
- 4. Engine oil pressure gauge
- Voltmeter gauge
- Locking caps on fuel and hydraulic fluid tanks
- Towing lockout which enables the machine to be towed short distances in the event of engine failure
- 8. Switches to prevent hoist and hopper damage

## Optional Equipment and Spare Parts Package: See page one.

Manufacturer's Identification: A durable identification plate stating the manufacturer's name, location, model, and other suitable information to identify the Beachcleaner for parts or repair is permanently attached to the frame.

Materials: All materials, parts and assemblies are new and are of current manufacture. Workmanship, fabrication and assembly are in conformance with standard manufacturing and engineering practices. Bolts are of sufficient length to assure a full thread nut. All bolts are fitted with self-locking nuts or with lock washers. All welds and welding practices conform to the latest American Welding Society Standards.

Warranty: 12 months on machine, including engine, pumps, motors and other components. Excludes normal maintenance and replacements wear parts, such as, but not limited to, electrical components, filters, oil, belts, chains, conveyor parts, digger points and screens.

<u>Disclaimer:</u> The Company reserves the right to make any changes deemed necessary to the above specifications without notice, and is not liable for unintentional errors in the specifications.