ORIGINAL**BELL**SOUTH

BellSouth Telecommunications, Inc. Suite 400 150 South Monroe Street Tallahassee, FL 32301-1556

October 31, 2002

marshall.criser@bellsouth.com

Marshall M. Criser III Vice President Regulatory & External Affairs

10

850 224 7798 Fax 850 224 5073

Mrs. Blanca S. Bayo Director, Division of The Commission Clerk and Administrative Services Florida Public Service Commission 2540 Shumard Oak Boulevard Tallahassee, Florida 32399

RE: Docket 020842-TP Request for approval of interconnection, unbundling, resale, and collocation agreement between BellSouth Telecommunications, Inc. and AmeriMex Communications, Corp.

Dear Ms. Bayo:

On July 30, 2002, BellSouth and AmeriMex Communications, Corp. filed an interconnection, unbundling, resale, and collocation agreement for Florida Public Service Commission approval. The subject of the cover letter of the filing was styled as referenced above.

However, in the filing of this agreement several pages of the original contract were inadvertently omitted from the filing, and the accompanying diskette contained an incorrect copy of the filing. Please, accept this letter and the attached pages and diskette as correction to the above referenced docket.

I appreciate your assistance in correcting the filing and record in question.

Very truly yours,

all M. Criser II Mars

Regulatory Vice President

RECEIVED OF RECORDS FPSC-BI

(LA)

DOCUMENT & MURREDATE

1970 OCT 31 8

FPSC-COMMUNICATION CLERK

| AUS. | |
|------|--|
| OAF | |
| CMP | |
| MOO | |
| CTR | |
| ECR | |
| GCL | |
| OPC | |
| MMS | |
| SEC | |
| OTH | |

1

| UNBUNDLE | D NETWORK ELEMENTS - Florida | | | | | | | | | | | | Attachment: | 2 | Exhibit: B | |
|----------|--|-------------|------------|----------|--|---|--------|---------|------------|--|---|-----------|---|---|---|---|
| CATEGORY | RATE ELEMENTS | interi m | Zone | BCS | USOC | | | 'ES(\$) | | | Svc Order Submitted Elec per LSR | Submitted | Charge - Manual Svc Order vs. Electronic- 1st | Charge - Manual Svc Order vs. Electronic- Add'i | Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st | Incremental Charge - Manual Svo Order vs. Electronic- Disc Add'i |
| | | ļ | | | | Rec | Nonrec | | | Disconnect | | | | Rates(\$) | | |
| | | 1 | <u> </u> | | | | First | Add'l | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| Non-F | ecurring Charges (NRC) Associated with UNE-P Centrex | | | | | | | | | | | | | | | |
| | NRC Conversion Currently Combined Switch-As-Is with allowed | | | UEP95 | USAC2 | 0.00 | 21 50 | 8.42 | | | | 11.90 | | | | • |
| | changes, per port Conversion of Existing Centrex Common Block, each | | <u> </u> | UEP95 | USAC2 | | 5.17 | 8.32 | | | | 11.90 | | · | | |
| | New Centrex Standard Common Block | | | UEP95 | MIACS | 0 00 | 618 82 | 0.5£ | | | | 11 90 | | | | |
| | New Centrex Customized Common Block | <u> </u> | | UEP95 | MIACC | 0 00 | 618 82 | | | | | 11.90 | | | | } |
| | NAR Establishment Charge, Per Occasion | | | UEP95 | URECA | 0.00 | 66.48 | | | | | 11.90 | | | | |
| UNE-F | CENTREX - DMS100 (Valid in All States) | | | | | | | | | ······································ | | | | | | 1 |
| | VG Loop/2-Wire Voice Grade Port (Centrex) Combo | | | | | | | | | | | | | | | 1 |
| | ort/Loop Combination Rates (Non-Design) | | | | | | | | | | | | | | | 1 |
| | 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex) Port Combo - | | | | 1 | | | | | | | | | | | |
| | Non-Design | L | 1 | UEP9D | ļ | 14.11 | | | | | | | | · | | |
| | 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | | | | 1 | | | | | | | | | | | |
| | Non-Design | | 2 | UEP9D | ļ | 18 23 | [| | | | · · · | | | | | |
| | 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | ļ | | |] | 33 04 | | | | | | | | | | |
| | Non-Design | | 3 | UEP9D | f | 33 04 | | | | | | | | | | |
| UNE F | ort/Loop Combination Rates (Design) | | | <u></u> | | ├ | | | | | | | | | | |
| | 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex) Port Combo | 1 | 1 | UEP9D | ł | 16 53 | 1 | | | | | | | | | |
| | Design 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | | { <u>'</u> | UEF 9D | ł | 10 33 | | | | | | | | | | |
| | Design | 1 | 2 | UEP9D | | 21.60 | | | | | | | | | | |
| | 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | 1 | <u> </u> - | | <u> · · · · · · · · · · · · · · · · · · ·</u> | | | | | | | | | | | |
| | Design | | 3 | UEP9D | 1 | 37.85 | | | | | | | | Í | | |
| | oop Rate | | | | | | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL 1) - Zone 1 | | | UEP9D | UECS1 | 12.94 | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL 1) - Zone 2 | | 2 | UEP9D | UECS1 | 17.06 | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL 1) - Zone 3 | | | UEP9D | UECS1 | 31.87 | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 1 | | | UEP9D | UECS2 | 15 36 | | | ļ <u> </u> | | | | | | | |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 2 | | | UEP9D | UECS2 | 20.43 | | | | · | | | | | | |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 3 | | 3 | UEP9D | UECS2 | 36.68 | | | | | | | | | | |
| | Port Rate | | — | | | l | | , | | | | | | | | |
| ALLS | TATES | | | UIEDOD | UEPYA | 1.17 | | | · | | | 11.90 | | | | |
| | 2-Wire Voice Grade Port (Centrex) Basic Local Area | L | <u> </u> | ÜEP9D | UEPTA | 1.17 | | | | | | 11.50 | | | | |
| | 2-Wire Voice Grade Port (Centrex 800 termination)Basic Local | | | UEP9D | UEPYB | 1.17 | | | | | | 11 90 | J | | | |
| | Area 2-Wire Voice Grade Port (Centrex / EBS-PSET)3Basic Local | | | | IOLF ID | | | | | ···· | | | | | | |
| ļ | Area | | 1 | UEP9D | UEPYC | 1.17 | | | | | | 11 90 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5009)3Basic Local | | <u> </u> | | | <u> </u> | | | | | | | | | | |
| | Area | | 1 | UEP9D | UEPYD | 1.17 | 1 | | | 1 | | 11.90 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5209))3 Basic Local | t | | | | | | | | | | | | | | |
| | Area | 1 | 1 | UEP9D | UEPYE | 1.17 | | | | | | 11 90 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5112))3 Basic Local | 1 | | | | | | | | | | | | | | |
| | Area | | | UEP9D | UEPYF | 1.17 | · | | | | | 11.90 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5312))3Basic Local | | | | | | | | | | | | | | | |
| | Area | | 4 | UEP9D | UEPYG | 1.17 | | | | | | 11.90 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5008))3 Basic Local | 1 | 1 | | | 1 1 | | | 1 | | | 44.00 | | | | |
| | Area | I | | UEP9D | UEPYT | 1.17 | | | <u> </u> | | | 11.90 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5208))3 Basic Local | 1 | 1 | UEP9D | UEPYU | 1 17 | 1 | | | | | 11.90 | | | | |
| | Area | <u> </u> | + | DEPSD | DEPTO | <u>{'-'</u> | | | | | | 11.50 | | | | |
| | 2-Wire Voice Grade Port (Centrex / EBS-M5216))3 Basic Local | 1 | 1 | UEP9D | UEPYV | 1 17 | | | | 1 | | 11 90 | 1 | | | |
| | Area 2-Wire Voice Grade Port (Centrex / EBS-M5316))3 Basic Local | t | + | 02.00 | 1 ···· | <u> </u> | | | | | | | | | | |
| | | 1 | 1 | UEP9D | UEPY3 | 1.17 | | | | | | 11 90 | | | | |
| | Area 2-Wire Voice Grade Port (Centrex with Caller ID) Basic Local | t | t | <u> </u> | 1 | 1 | | · | | | | | | | | |
| | Area | 1 | 1 | UEP9D | UEPYH | 1 17 | | | | | | 11.90 | | | | |
| | 2-Wire Voice Grade Port (Centrex/Caller ID/Msg Wtg Lamp | 1 | 1 | | | | | | | | | | | | | |
| | Indication))3 Basic Local Area | | | UEP9D | UEPYW | 1 17 | | | L, | | | 11 90 | | | | |
| | | Т. | | T | 1 | | | | | | | | | | | |
| | 2-Wire Voice Grade Port (Centrex/Msg Wtg Lamp Indication))3 | | | UEP9D | UEPYJ | 1 17 | | | | | | 11 90 | | | | |

| INPI | | D NETWORK ELEMENTS - Georgia | | | | | | | | | | | | Attachment: | 2 | Exhibit: 8 | |
|----------|----------|---|-------------|----------|-------------------|------------|-------------|----------------|--------------|---------------------|-------|---|-----------|--|--|-------------------------|---|
| CATEG | | RATE ELEMENTS | interi m | Zone | BCS | USOC | | RAT | res(\$) | e de la munda delen | | Svc Order Submitted Elec per LSR | Submitted | Incremental Charge - Manual Svc Order vs. Electronic- 18t | Incrementat Charge - Manual Svc Order vs. Electronic- Add'l | Incremental Charge - | Incremental Charge - Manual Svc Order vs. Electronic- Disc Add'I |
| | | | | | | | Rec | Nonrec | | Nonrecurring | | | | | Rates(\$) | | |
| | | | | | | | ney | First | Add'l | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| | | Interoffice Channel - Dedicated Transport- 2- Wire Voice Grade - | | | | | | | | | | | | | | | |
| | | Facility Termination per month | | <u> </u> | UITVX | U1TV2 | 17 07 | 79.61 | 36.08 | | | | | 18 94 | 18 94 | | |
| | | Interoffice Channel - Dedicated Transpor t- 2-Wire Voice Grade Rev Bat, - Per Mile per month | | | UITVX | 1L5XX | 0.0222 | | | | | | | | | | |
| | | Interoffice Channel - Dedicated Transport- 2- Wire VG Rev Bat Facility Termination per month | | | ⊎itvx | U1TR2 | 17.07 | 79.61 | 36 08 | | | | | 18 94 | 18 94 | | |
| | | Interoffice Channel - Dedicated Transport - 56 kbps - per mile | | <u> </u> | | | | | | | | | | | | | |
| | | per month Interoffice Channel - Dedicated Transport - 56 kbps - Facility | | | UITDX | 1L5XX | 0 0222 | | | | | | | | | | |
| | | Termination per month | | | UITDX | U1TD5 | 16.45 | 79.61 | 36 08 | | | | | 18.94 | 18 94 | | |
| | | Interoffice Channel - Dedicated Transport - 64 kbps - per mile per month | | | UITDX | 1L5XX | 0.0222 | | | | | | | | | | |
| | | Interoffice Channel - Dedicated Transport - 64 kbps - Facility | | | | | | | | | | | | | | | |
| | | Termination per month Interoffice Channel - Dedicated Channel - DS1 - Per Mile per | | – | UITDX | U1TD6 | 16.45 | 79 61 | 36.08 | | | | | 18 94 | 18 94 | | |
| | | month | | | UITDI | 1L5XX | 0.4523 | | | | | | | | | | |
| | | Interoffice Channel - Dedicated Tranport - DS1 - Facility Termination per month | | | UITDI | UITEI | 78 47 | 147.07 | 111.75 | | | | | 18.94 | 18.94 | | |
| | | Interoffice Channel - Dedicated Transport - DS3 - Per Mile per month | | | U1TD3 | 1L5XX | 2.72 | | | | | | | | | | |
| | | Interofice Channel - Dedicated Transport - DS3 - Facility Termination per month | | | U1TD3 | U1TF3 | 788 00 | 511.10 | 330 77 | | | | | 37 55 | 37 55 | 18 03 | 18 03 |
| | <u> </u> | Interoffice Channel - Dedicated Transport - STS-1 - Per Mile per month | | | U1TS1 | 1L5XX | 2.72 | | | | | | | | | | |
| | <u> </u> | Interofice Channel - Dedicated Transport - STS-1 - Facility Termination per month | | 1- | UITSI | UITES | 783 63 | 511.10 | 449 91 | | | | | 61.19 | 61 19 | 3.17 | 3 17 |
| | 1 CCA | CHANNEL - DEDICATED TRANSPORT | t | + | | | | | | | | | | | | | |
| | NOTE | LOCAL CHANNEL DEDICATED TRANSPORT - minimum billin | g perio | d - bel | ow DS3=one month, | DS3/STS-1= | four months | | | | | | | | | | |
| | 1012 | Local Channel - Dedicated - 2-Wire Voice Grade Per Month | [| | ULDVX | ULDV2 | 13 91 | 382.95 | 62.40 | | | L | | 18.94 | 8.42 | | |
| | | Local Channel - Dedicated - 2-Wire Voice Grade Rev Bat per | | | ULDVX | ULDR2 | 13 91 | 382.95 | 62.40 | | | | | 18 94 | 18 94 | | |
| | t | Local Channel - Dedicated - 4-Wire Voice Grade per month | | | UNDVX | ULDV4 | 14 99 | 368 44 | 64 05 | | | | | 18 94 | 8 42 44 22 | 18.03 | 18 03 |
| | | Local Channel - Dedicated - DS1 per month | | 1 | ULDD1 | ULDF1 | 38 36 | 356.15 | 312.89 | | | | | 44 22 | 44 22 | 10.03 | 18 03 |
| | | Local Channel - Dedicated - DS3 - Per Mile per month | L | _ | ULDD3 | 1L5NC | 6.92 | | | | | | | | | · | |
| | | Local Channel - Dedicated - DS3 - Facility Termination per month | | | ULDD3 | ULDF3 | 515.91 | 639.50 | 426 31 | | | ļ | | 37 55 | 37.55 | 18 03 | 18 03 |
| | | Local Channel - Dedicated - STS-1- Per Mile per month | | | ULDS1 | 1L5NC | 6.92 | | | + | | + | <u> </u> | · | | | |
| | | Local Channel - Dedicated - STS-1 - Facility Termination per month | ļ | | ULDS1 | ULDES | 517 56 | 639 50 | 426 31 | | | | | 18.94 | 18 94 | | |
| MULT | PLEXE | RS | + | + | | MQ1 | 126.22 | 198.22 | 123 59 | + | [| + | <u> </u> | 14 75 | 6.55 | 10.70 | † |
| | | Channelization - DS1 to DS0 Channel System | + | + | | | 160.66 | 100.22 | 1.0.00 | | | | | 1 | | | |
| | | OCU-DP COCI (data) - DS1 to DS0 Channel System - per month (2.4-64kbs) | | | UDL | 1D1DD | 1.86 | 12.02 | 8.66 | ļ | | | | 14.75 | 6.55 | 10 60 | |
| | | 2-wire ISDN COCI (BRITE) - DS1 to DS0 Channel System - per month | | | UDN | UC1CA | 3.37 | 12 02 12 02 | 8 66 8.66 | | | | | 14.75 14.75 | 6.55 6.55 | 10 60 10 60 | |
| | | Voice Grade COCI - DS1 to DS0 Channel System - per month | | + | UEA UXTD3 | MQ3 | 1.17 | 265 91 | 188 78 | | t | | | 14.75 | 6 55 | | |
| | | DS3 to DS1 Channel System per month | + | + | UXTS1 | MQ3 | 182.04 | 265.91 | 188.78 | | | 1 | | 18.94 | 18.94 | | |
| L | | STS1 to DS1 Channel System per month DS3 Interface Unit (DS1 COCI) used with Loop per month | + | + | USL | UCIDI | 11.02 | 12.02 | 8.66 | | | | | 14.75 | 6 55 | 10 60 | |
| <u> </u> | | DS3 Interface Unit (DS1 COCI) used with Local Channel per | 1 | | ULDD1 | UC1D1 | 11.02 | 12.02 | 8 66 | | | | | 14.75 | 6 55 | | |
| | + | month DS3 Interface Unit (DS1 COCI) used with Interoffice Channel | <u>†</u> | \top | | UC1D1 | 11 02 | 12.02 | 8 66 | 1 | | | | 14.75 | 6 55 | | |
| DARK | FIBER | per month | 1 | 1 | | | | | | | | | | | | ···· ··· ··· | |
| | | Dark Fiber, Four Fiber Strands, Per Route Mile or Fraction | | 1 | UDF | 1L5DC | 44 22 | ł | l | | 1 | | | | | | |
| —— | + | Thereof per month - Local Channel NRC Dark Fiber - Local Channel | + | + | UDF | UDFC4 | | 1,355 29 | 273 69 | | | | | 18 94 | 18 94 | | |
| | + | Dark Fiber, Four Fiber Strands, Per Route Mile or Fraction | + | 1 | | 1 | | | | | | 1 | | | | | |
| | | Thereof per month - Interoffice Channel | | | UDF | 1L5DF | 44.22 | | | | | | | | | l | |

.

-

| UNBUNDLI | ED NETWORK ELEMENTS - Georgia | | | | | | | | | | | | Attachment: | 2 | Exhibit: B | r |
|--------------|--|-------------|----------------|--------|--------|----------|---------------|-----------|---------|--------------|------------|---|----------------|-------------------------|-------------------------|---|
| CATEGORY | RATE ELEMENTS | Interi m | Zone | BCS | USOC | | RA | TES(\$) | | | | Svc Order Submitted Manually per LSR | Incremental | Incremental Charge - | Incremental Charge - | Incremental Charge - Manual Svo Order vs. Electronic- Disc Add'I |
| · | + <u> </u> | | + | | | <u> </u> | Nooro | number of | Nemeral | | | | | | | |
| i | | | + | | | Rec | Nonre | | | g Disconnect | | | | Rates(\$) | | |
| · | 2-Wire Voice Grade Loop / Line Port Combination - Switch with | <u> </u> | + | | | | First | Add'l | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| i 1 | change | 1 | 1 | UEPRX | USACC | 1 | 41.50 | 41.50 | | | | | 00.07 | 7.00 | | |
| ADD | TIONAL NRCs | 1 | + | | 00000 | <u> </u> | 41.50 | 41.50 | | | | | 33.67 | 7.88 | 11.17 | 391 |
| | NRC - 2-Wire Voice Grade Loop/Line Port Combination - | | t | | | | | | | | | | | | | |
| 1 | Subsequent | ł | 1 | UEPRX | USAS2 | 0.00 | 0.00 | 0.00 | Į | 1 | | | 33 67 | 7.88 | 11.17 | 3 91 |
| 2-WIF | RE VOICE GRADE LOOP WITH 2-WIRE LINE PORT (BUS) | 1 | | | | | | | | | | | 00 07 | 7.00 | | 391 |
| UNE | Port/Loop Combination Rates | | 1 | | | | | · · · · · | | 1 | | | | | | |
| | 2-Wire VG Loop/Port Combo - Zone 1 | | 1 | | | 24.80 | | | | | | | | | | |
| | 2-Wire VG Loop/Port Combo - Zone 2 | 1 | 2 | | | 26.47 | | | | 1 | | | | | | |
| | 2-Wire VG Loop/Port Combo - Zone 3 | | 3 | | | 33.83 | | | | | | | | | | |
| UNEI | Loop Rates | 1 | <u> </u> | | | | | | | | | | | | | |
| <u> </u> | 2-Wire Voice Grade Loop (SL1) - Zone 1 | | 11 | UEPBX | UEPLX | 10.80 | | | | | | | | | | |
| _ | 2-Wire Voice Grade Loop (SL1) - Zone 2 | <u> </u> | 2 | UEPBX | UEPLX | 12.47 | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL1) - Zone 3 | ← | 3 | UEPBX | UEPLX | 19.83 | | | | | | | | | | |
| 2-Wife | 2-Wire voice unbundled port without Caller ID - bus | + | | UEPBX | UEPBL | 14.00 | 90 00 | 90.00 | | | | | | 7.05 | | |
| · | 2-Wire voice unbundled port with Caller + E484 ID - bus | t | + | UEPBX | UEPBC | 14.00 | 90.00 | 90.00 | | | <u>├</u> i | | 33 67 | 7 88 | 11 17 | 3.91 |
| _ | 2-Wire voice unbundled port outgoing only - bus | | <u>†</u> | UEPBX | UEPBO | 14.00 | 90.00 | 90.00 | | | | · · · · | 33.67 33.67 | 7 88 | 11.17 | 3.91 |
| | | | + | ULT DA | DEFBO | 14.00 | 5000 | 90.00 | l | | | | 33.67 | 7 88 | 11.17 | 3.91 |
| | Local Number Portability (1 per port) | <u> </u> | + | UEPBX | LNPCX | 0.35 | | | | | | | | | | |
| FEAT | URES | | t | | | 0.00 | | | | | | | | | | |
| r | All Features Offered | | 1 | UEPBX | UEPVF | 0.00 | 0.00 | 0.00 | | | | | 33 67 | 7.88 | 11 17 | 3 91 |
| NONF | RECURRING CHARGES - CURRENTLY COMBINED | | 1 | | | | | | | | | | | 7.00 | | - 331 |
| | | | 1 | | | | | | | | | | | | | |
| | 2-Wire Voice Grade Loop / Line Port Combination - Switch-as-is | | | UEPBX | USAC2 | | 41.50 | 41.50 | | | | | 33 67 | 7.88 | 11 17 | 3 91 |
| | 2-Wire Voice Grade Loop / Line Port Combination - Switch with | | | | 1 | | | | | | | | | | | |
| | change | | | UEPBX | USACC | | 41.50 | 41 50 | | | | | 33 67 | 7.88 | 11.17 | 3.91 |
| ADDI | TIONAL NRCs | ļ | + | l | 1 | | | | | | | | | | | |
| 1 | NRC - 2-Wire Voice Grade Loop/Line Port Combination - | | 1 | ł | | | | | | | | | | | | |
| | Subsequent | <u>}</u> | | UEPBX | USAS2 | | 0.00 | 0.00 | | | | | 33 67 | 7.88 | 11.17 | 3 91 |
| 2-WIR | RE VOICE GRADE LOOP WITH 2-WIRE LINE PORT (RES - PBX) | ····- | | | | | | | | | | | | | | |
| UNEF | Port/Loop Combination Rates | | 1 | | | 04.00 | | | | | | | | | | |
| | 2-Wire VG Loop/Port Combo - Zone 1 | | 2 | | | 24.80 | | | | | | | | | | |
| <u>⊢−−</u> ∔ | 2-Wire VG Loop/Port Combo - Zone 2 2-Wire VG Loop/PortCombo - Zone 3 | | 3 | · | | 33.83 | | | | | | | | | | |
| | Loop Rates | | ᡰ᠊᠆ | | | | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL1) - Zone 1 | t | · | UEPRG | UEPLX | 10.80 | | | | | | | | | | |
| h | 2-Wire Voice Grade Loop (SL1) - Zone 2 | 1 | | UEPRG | UEPLX | 12.47 | | | | | | | | | | |
| | 2-Wire Voice Grade Loop (SL1) - Zone 3 | | | UEPRG | UEPLX | 19 83 | | | | | | | | | | |
| 2-Wir | e Voice Grade Line Port Rates (RES - PBX) | 1 | I | | | | | | | | | | | | | |
| | 2-Wire VG Unbundled Combination 2-Way PBX Trunk Port - | | | | | | | | | | | | | | | |
| | Res | | | UEPRG | UEPRD | 14.00 | 90.00 | 90.00 | | | | | 33.67 | 7 88 | 11.17 | 3.91 |
| LOC/ | AL NUMBER PORTABILITY | | | | | | | | | | | | | | | |
| | Local Number Portability (1 per port) | L | | UEPRG | LNPCP | 3.15 | 0.00 | 0.00 | | | | | | | | |
| FEAT | URES | | 1 | | | | | | | | | | | | | |
| | All Features Offered | | ļ | UEPRG | UEPVF | 0.00 | 0.00 | 0.00 | | | | | 33 67 | 7 88 | 11.17 | 3 91 |
| NONP | RECURRING CHARGES - CURRENTLY COMBINED | <u> </u> | | | + | | | | | | | | | | | |
| 1 | | 1 | | UEDDO | 115400 | | 44.00 | 44.50 | | | | | | 7.00 | | |
| ├ | 2-Wire Voice Grade Loop/ Line Port Combination - Switch-As-Is | l | ł | UEPRG | USAC2 | | 41.50 | 41.50 | | | | | 33.67 | 7.88 | 11.17 | 3.91 |
| 4 | 2-Wire Voice Grade Loop/ Line Port Combination - Switch with | | | UEPRG | USACC | 1 | 41.50 | 41.50 | | | | | 22.67 | 7.88 | | 2.01 |
| i | Change | — — | <u> </u> | ourna | USAUC | | 41.50 | 41.50 | | | | | 33.67 | 7.86 | 11.17 | 3 91 |
| A D D D | | | 1 | | | | | | | | | | | | | |
| ADD | TIONAL NRCs | | 1 | | 1 | | | | | | | | | | | |
| ADDI | 2 Wire Loop/Line Side Port Combination - Non feature - | | | | | | 0.00 | | | | | | 33.67 | 7 89 | 11 17 | 3.01 |
| ADDI | 2 Wire Loop/Line Side Port Combination - Non feature - Subsequent Activity- Nonrecurring | | | | | | 0.00 | 0.00 | | | | | 33 67 | 7.88 | 11.17 | 3 91 |
| ADD | 2 Wire Loop/Line Side Port Combination - Non feature - Subsequent Activity- Nonrecurring PBX Subsequent Activity - Change/Rearrange Multiline Hunt | | | | | | | 0.00 | | | | | | | | |
| | 2 Wire Loop/Line Side Port Combination - Non feature - Subsequent Activity - Nonrecurring PBX Subsequent Activity - Change/Rearrange Multiline Hunt Group | | | | | | 0 00 14.64 | | | | | | 33 67 19.99 | 7.88 19 99 | 11.17 19.99 | 3 91 19 99 |
| 2-WIF | 2 Wire Loop/Line Side Port Combination - Non feature - Subsequent Activity- Nonrecurring PBX Subsequent Activity - Change/Rearrange Multiline Hunt | | | | | | | | | | | | | | | |

| UNBUNDL | ED NETWORK ELEMENTS - Georgia | | | | | | | | | | | | Attachment: | 2 | Exhibit: B | |
|---------------------------------------|--|-------------|------------|----------------------|----------------|----------------|--------|---------|--------------|---------------------------------------|---|---|---|--|---|--|
| CATEGORY | RATE ELEMENTS | Interi m | Zone | BCS | usoc | | | res(\$) | | | Svc Order Submitted Elec per LSR | Svc Order Submitted Manually per LSR | Charge - Manual Svc Order vs. Electronic- 1st | Incremental Charge - Manual Svc Order vs. Electronic- Add'l | Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st | Incrementa Charge - Manual Sv Order vs. Electronic Disc Add'i |
| | | | | | | Rec | Nonrec | | Nonrecurring | | | | | Rates(\$) | | |
| | | | | | | | First | Add'i | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| | Interoffice Channel Mileage · Fixed rate 0-8 miles (Facilities | 1 | 1 | | | | | | 1 | | | | | | | |
| | Termination) | | | UEPDC | 1LNO1 | 78.47 | 147.07 | 11175 | | | | | 19 99 | 19.99 | | ļ |
| | | | 1 | | | | | | | | | | | • | | |
| | Interoffice Channel Mileage - Additional rate per mile - 0-8 miles | | | UEPDC | 1LNOA | 0.4523 | 0.00 | 0 00 | | | | | | | | |
| | Interoffice Channel Mileage - Fixed rate 9-25 miles (Facilities | 1 | | UEPDC | 1LNO2 | 0.00 | 0.00 | 0.00 | | | | | | | | |
| | Termination) | | | | 10102 | | 0.00 | 0.00 | | | | | | | | |
| | mites | | | UEPDC | 1LNOB | 0 4523 | 0.00 | 0.00 | | | | | | | | 1 |
| | Interoffice Channel Mileage - Fixed rate 25+ miles (Facilities | 1 | | 02100 | 1.5105 | 04020 | 0.00 | 0.00 | | | | | | | | |
| | Temination) | | | UEPDC | 1LNO3 | 0.00 | 0.00 | 0.00 | | | | | | | | |
| | | | 1 | | | | | | | | | | | | | |
| | Interoffice Channel Mileage - Additional rate per mile - 25+ miles | | 1 | UEPDC | 1LNOC | 0.4523 | 0.00 | 0 00 | | | L | | | | | |
| | Local Number Portability, per DS0 Activated | L | | UEPDC | LNPCP | 3.15 | | | | | | | | | | |
| | Central Office Termininating Point | | | UEPDC | CTG | 0.00 | | | | | | | | | | |
| | RE DS1 LOOP WITH CHANNELIZATION WITH PORT | J | | | | | | | | | | | | | | |
| Syste | em is 1 DS1 Loop, 1 D4 Channel Bank, and up to 24 Feature Act | tivation | <u>د</u> | L | | | | | | | | | | | | l |
| | stem can have various rate combinations based on type and nu | imber of | f ports | used | | | | | | | | | | | | |
| UNE | DS1 Loop | 1. | | UEPMG | USLDC | 55 53 | 0.00 | 0.00 | | | | | | | | ł |
| | 4-Wire DS1 Loop - UNE Zone 1 | <u> </u> | | UEPMG | USLDC | 64 13 | 0.00 | 0.00 | | | | | | | | <u> </u> |
| | 4-Wire DS1 Loop - UNE Zone 2 | | | UEPMG | USLDC | 101.93 | 0.00 | 0.00 | | | | | | | | |
| | 4-Wire DS1 Loop - UNE Zone 3 | | <u> ~</u> | UEFING | | 101.33 | | 0.00 | | | | | | | | |
| UNE | DSO Channelization Capacities (D4 Channel Bank Configuration 24 DSO Channel Capacity - 1 per DS1 | T | | UEPMG | VUM24 | 102 64 | 0 00 | 0.00 | | | | | 19 99 | 19 99 | | |
| | 48 DSO Channel Capacity - 1 per 2 DS1s | + | + | UEPMG | VUM48 | 205 28 | 0.00 | 0.00 | 1 | | | | 19 99 | 19.99 | | |
| | 96 DSO Channel Capacity - 1per 4 DS1s | | | UEPMG | VUM96 | 410.56 | 0.00 | 0.00 | | · · · · · · · · · · · · · · · · · · · | | | 19.99 | 19.99 | | |
| | 144 DS0 Channel Capacity - 1 per 6 DS1s | | 1 | UEPMG | VUM14 | 615.84 | 0 00 | 0.00 | | | | | 19.99 | 19.99 | | |
| | 192 DS0 Channel Capacity -1 per 8 DS1s | | 1 | UEPMG | VUM19 | 821.12 | 0 00 | 0 00 | | | | | 19 99 | 19.99 | | |
| | 240 DS0 Channel Capacity - 1 per 10 DS1s | | | UEPMG | VUM20 | 1,026.40 | 0 00 | 0.00 | | | | | 19 99 | 19 99 | | |
| | 288 DS0 Channel Capacity - 1 per 12 DS1s | | | UEPMG | VUM28 | 1,231.68 | 0.00 | 0.00 | | | | | 19 99 | 19.99 | | I |
| | 384 DS0 Channel Capacity - 1 per 16 DS1s | | | UEPMG | VUM38 | 1,642.24 | 0.00 | 0.00 | | | | | 19 99 | 19.99 | | |
| | 480 DS0 Channel Capacity - 1 per 20 DS1s | | | UEPMG | VUM40 | 2,052.80 | 0.00 | 0.00 | | | | <u> </u> | 19 99 | 19.99 | | l |
| | 576 DS0 Channel Capacity -1 per 24 DS1s | 1 | | ÜEPMG | VUM57 | 2,463.36 | 0.00 | 0.00 | | | | | 19 99 | 19.99 | | |
| | 672 DS0 Channel Capacity - 1 per 28 DS1s | <u> </u> | | UEPMG | VUM67 | 2,873 92 | 0.00 | 0.00 | | | | | 19.99 | 19.99 | | |
| Non- | Recurring Charges (NRC) Associated with 4-Wire DS1 Loop with | th Chan | neliztio | in with Port - Conve | orsion Charge | Based on a Sy | stem | | | | · · · · · | | | | | |
| A Mi | nimum System configuration is One (1) DS1, One (1) D4 Channel | el Bank, | , and U | p To 24 DSO Ports v | with Feature A | ctivations. | · | | | | | · · · | | | | ····- |
| Muit | iples of this configuration functioning as one are considered A | dd'i atte | er the m | ninimum system cor | | countea. | | | | | | | | | | t |
| | NRC - Conversion (Currently Combined) with or without | | | UEPMG | USAC4 | 0.00 | 450.00 | 50.00 | | | | | 19.99 | 19.99 | | 1 |
| | BellSouth Allowed Changes - Top 8 MSAs Only em Additions Where Currently Combined and New (Not Current | Hy Com | hined) | | 100/107 | 0.00 | 400.00 | 00.00 | | | | | | | | |
| Syst | op 8 MSAs and AL, FL, and NC Only | 1 | 1 | | | | | | | | | [| | | | |
| | 1 DS1/D4 Channel Bank - Add NRC for each Port and Assoc | - | + | | 1 | | | | | | 1 | | | | | |
| ł | Fea Activation - | | 1 | UEPMG | VUMD4 | 0.00 | 950.00 | 600.00 | 200 00 | 30 00 | 1 | | 19 99 | 19 99 | | |
| Bind | blar 8 Zero Substitution | | | | | | | | | | | 1 | | | | |
| | Clear Channel Capability Format, superframe - Subsequent | | | r | | | | | | | 1 | | | | | |
| 1 | Activity Only | L | | UEPMG | CCOSF | 0.00 | 0.00 | 600 00 | | | ļ | L | | | | |
| | Clear Channel Capability Format - Extended Superframe - | | | | | | | | | 1 | | 1 | | | | 1 |
| | Subsequent Activity Only | 1 | | UEPMG | CCOEF | 0.00 | 0.00 | 600.00 | | | <u> </u> | | | | | |
| Alter | mate Mark Inversion (AMI) | 1 | | | - | | | | | | | <u> </u> | | | | <u> </u> |
| | Superframe Format | | | UEPMG | MCOSF | 0.00 | 0.00 | 0.00 | | l | | | | | | <u> </u> |
| | Extended Superframe Format | | - Darf | ÚEPMG | MCOPO | 0.00 | 0.00 | 0.00 | | | | <u> </u> | | | | |
| Exct | nange Ports Associated with 4-Wire DS1 Loop with Channelizat | ion witi | Port | · | + | | | | | | | | | | | |
| Exct | nange Ports | | + | <u>+</u> | | | | | | | <u> </u> | | | | | |
| | Las Orde Combinedian Channel and DDV Terrals Ded. Rusinger | 1 | | UEPPX | UEPCX | 14 00 | 0.00 | 0.00 | 0.00 | 0.00 | ŀ | 1 | 33 67 | 7.88 | | 1 |
| | Line Side Combination Channelized PBX Trunk Port - Business Line Side Outward Channelized PBX Trunk Port - Business | | + | UEPPX | UEPOX | 14.00 | 0.00 | 0.00 | 0.00 | 0.00 | | <u> </u> | 33 67 | 7.88 | | |
| · · · · · · · · · · · · · · · · · · · | ILINE SIDE OUTWARD CRANNELZED FOX TIURK FUT . DUSINESS | 1 | | | 100100 | 17.00 | 0.00 | 0.00 | | | <u> </u> | <u> </u> | | | | |
| | | | | | | | | | | | | | | | | |
| | | , | | UEPPX | UEP1X | 14.00 | 0.00 | 0.00 | 0.00 | 0.00 | | | 33.67 | 7 88 | | |
| | Line Side Inward Only Channelized PBX Trunk Port without DID 2-Wire Trunk Side Unbundled Channelized DID Trunk Port | , | ļ | | UEP1X | 14.00 83 00 | 0.00 | 0.00 | | 0.00 | | | 33.67 33.67 | 7 88 7 88 | | |

į.

| ATEGORY | RATE ELEMENTS | Interi | | | | | | | | | Svc Order Submitted | | Incremental Charge - | Incremental Charge - | Incremental Charge - | Incrementa Charge - |
|----------|---|----------|---------|----------------|----------------|--------|--------|---------|--------------|---------|------------------------|---------------------|---|---|-------------------------|--|
| | | m | Zone | BCS | USOC | | | 'ES(\$) | | | Elec per LSR | Manually per LSR | Manual Svc Order vs. Electronic- 1st | Manual Svc Order vs. Electronic- Add'i | | Manual Sv Order vs. Electronic Disc Add |
| | | | | | | Rec | Nonrec | | Nonrecurring | | | | | Rates(\$) | | |
| | | | | | | | First | Add'l | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| | Unbundled Network Access Register - Combination | | | UEP95 UEP95 | UARCX UAR1X | 0.00 | 0.00 | 0.00 | | | | 7.86 | | | | |
| | Unbundled Network Access Register - Indial | | ł | UEP95 | UAROX | 0.00 | 0.00 | 0.00 | | | | 7.86 | | | | · |
| Misce | Unbundled Network Access Register - Outdial | <u> </u> | | UEF85 | UNNUA | 0.00 | 0.00 | 0.00 | | | · | 1.00 | | | | |
| | Trunk Side | | | | 1 | | | | | | | | | ~ | | |
| | Trunk Side Terminations, each | | | UEP95 | CEND6 | 10 51 | 92.18 | 15 82 | 52 16 | 5.30 | | 7.86 | | | | |
| 4-Wire | e Digital (1.544 Megabita) | | | | | | | | | | | | | | | |
| | DS‡ Circuit Terminations, each | | | UEP95 | M1HD1 | 74 77 | 164.86 | 77.74 | 60 69 | 3.86 | | 7.86 | | | | |
| | DS0 Channels Activated, each | | | UEP95 | M1HDO | 0.00 | 15.09 | | | | | 7.86 | | | | |
| Intero | ffice Channel Mileage - 2-Wire | | | UEP95 | MIGBĆ | 29,11 | | | | | | 7.86 | | | | |
| <u> </u> | Interoffice Channel Facilities Termination Interoffice Channel mileage, per mile or fraction of mile | <u> </u> | | UEP95 | MIGBO | 0.01 | | | | | | 7.86 | | | | |
| Fastur | re Activations (DS0) Centrex Loops on Channelized DS1 Service | | | | | | | | | | | , | | | | <u> </u> |
| | annel Bank Feature Activations | <u> </u> | | | t | | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank Centrex Loop Slot | | | UEP95 | 1PQWS | 0 62 | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank FX line Side Loop Slot | | | UEP95 | 1PQW6 | , 0.62 | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank FX Trunk Side Loop Slot | | | UEP95 | 1PQW7 | 0.62 | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank Centrex Loop Slot - Different Wire Center | | | UEP95 | 1PQWP | 0.62 | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank Private Line Loop Slot | | | UEP95 | 1PQWV | 0.62 | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank Tjie Line/Trunk Loop Słot | | | UEP95 | 1PQWQ | 0.62 | | | | | | 7.86 | | | | |
| | Feature Activation on D-4 Channel Bank WATS Loop Slot | | | UEP95 | 1PQWA | 0.62 | | | | | | 7.86 | | | | |
| Non-F | Recurring Charges (NRC) Associated with UNE-P Centrex | | | | | | | | | | | | | | | |
| | NRC Conversion Currently Combined Switch-As-Is with allowed changes, per port | | | UEP95 | USAC2 | | 0.102 | 0.102 | | | | 786 | | | | |
| | Conversion of Existing Centrex Common Block, each | | | UEP95 | USACN | | 18 95 | 8.32 | | | | 7 86 | | | | |
| | New Centrex Standard Common Block | | | UEP95 | MIACS | 0.00 | 669.80 | 78.32 | 111.05 | 13.27 | | 7.86 | | | | |
| | New Centrex Customized Common Block | | | UEP95 | MIACC | 0.00 | 669.80 | 78.32 | 111.05 | 13.27 | | 7.66 | | | | |
| | NAR Establishment Charge, Per Occasion | <u> </u> | | UEP95 | URECA | 0.00 | 72.75 | | | | | 7.86 | | | | |
| | P CENTREX - DMS100 (Valid in All States) | | | | L | | | | | | | | | | | |
| 2-Wire | VG Loop/2-Wire Voice Grade Port (Centrex) Combo | <u> </u> | i | | | | | | | | | | | | | |
| | Port/Loop Combination Rates (Non-Design) 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex) Port Combo | | | UEP9D | | 10.79 | | | | | | | | | | |
| | Non-Design 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | | | UEP9D | | 15.52 | | | | | | , / | | | | |
| <u> </u> | Non-Design 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | | 2 | | | | | | | | | | | | | |
| | Non-Design | ┝── | 3 | UEP9D | <u> </u> | 31.74 | | | | | <u> </u> | · · · | | | ł | |
| | Port/Loop Combination Rates (Design) 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex) Port Combo - Device Combined Combine Combined Combined Comb | | 1 | UEP9D | 1 | 13.82 | | | | | | | | | | |
| | Design 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - Design | | | UEP9D | | 13.62 | | | | | | | | | | |
| | Design 2-Wire VG Loop/2-Wire Voice Grade Port (Centrex)Port Combo - | | 1 | | 1 | | | | | | | | | | | <u> </u> |
| <u> </u> | Design | <u> </u> | 3 | UEP9D | | 34.37 | | | ├ | | | t | | | | |
| | Loop Rate 2-Wire Voice Grade Loop (SL 1) - Zone 1 | | 1 | UEP9D | UECS1 | 9.64 | | | | | | 7.86 | | l | | 1 |
| | 2-Wire Voice Grade Loop (SL 1) - Zone 2 | <u> </u> | 2 | UEP9D | UECS1 | 14.37 | | | | · · · · | | 7 86 | | | | |
| | 2-Wire Voice Grade Loop (SL 1) - Zone 3 | · · · · | | UEP9D | UECSI | 30.59 | | | | | | 7.86 | | 1 | | |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 1 | | 1 | UEP9D | UECS2 | 12.67 | | | | | | 7.86 | | | | |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 2 | | 2 | UEP9D | UECS2 | 17.45 | | | | | | 7.86 | | | | |
| | | 1 | 1 0 | UEP9D | UEC\$2 | 33.22 | | | 1 | | | 7.86 | | | | 1 |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 3 | L | 3 | UEF90 | 02002 | 33.22 | | | | | | /.00 | | | | <u> </u> |
| | 2-Wire Voice Grade Loop (SL 2) - Zone 3 Port Rate STATES | | | UEF 90 | 02032 | 33.22 | | | | | | 7.80 | | | | |

,

| ADDI INICH / | ED NETWORK ELEMENTS - Mississippi | | | | | | | | | | | | | Attachment: | | Exhibit: B | . |
|--------------|---|-------------|--------------|--------|---------|----------|----------|----------|----------|--------------|----------|----------|---|--|--|---|--------------------------------|
| ATEGORY | RATE ELEMENTS | Interi M | Zone | B | cs | USOC | | RAT | "ES(\$) | | | | Svc Order Submitted Manually per LSR | Incremental Charge - Manual Svc Order vs. Electronic- 1st | Incremental Charge - Manual Svc Order vs. Electronic- Add'l | Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st | Charge Manual S Order ve |
| | | | | | | | Rec | Nonrec | urring | Nonrecurring | | | | | Rates(\$) | L | |
| | | | | | | | HeG | First | Add'l | Finst | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| Teler | phone Number/Trunk Group Establisment Charges | | | | | | | | | | | | 15.75 | | | 197 | + |
| | DID Trunk Termination (One Per Port) | 1 | | UEPPX | | NDT | 0.00 | 0 00 | 0.00 | | | | 15.75 | | | 197 | |
| | Additional DID Numbers for each Group of 20 DID Numbers | 1 | | UEPPX | | ND4 | 0 00 | 0.00 | 0.00 | L | | | 15.75 | | | 1.97 | |
| | DID Numbers, Non- consecutive DID Numbers , Per Number | | | UEPPX | | ND5 | 0.00 | 0.00 | 0.00 | | | ł | 15.75 | | | 1.57 | |
| | Reserve Non-Consecutive DID numbers | ļ | | UEPPX | | ND6 | 0.00 | 0.00 | 0.00 | | | | 15 75 | | | 1 97 | |
| | Reserve DID Numbers | L | | UEPPX | | NDV | 0.00 | 0.00 | 0.00 | | | + | 1575 | | - | | + |
| LOC/ | AL NUMBER PORTABILITY | | | | | | 0.15 | 0.00 | 0.00 | | | + | | | | | + |
| | Local Number Portability (1 per port) | <u> </u> | | UEPPX | | LNPCP | 3.15 | 0.00 | 0.00 | | | ╄───── | | | | | + |
| 2-WI | RE ISDN DIGITAL GRADE LOOP WITH 2-WIRE ISDN DIGITAL L | NE SID | E PORT | | | | | | | | | | | | | | + |
| UNE | Port/Loop Combination Rates | | | | | | | | | | | | | | | <u> </u> | |
| | 2W ISDN Digital Grade Loop/2W ISDN Digital Line Side Port - | | 1 | UEPPB | UEPPR | | 28.59 | | | | | <u> </u> | | | | | |
| | UNE Zone 1 2W ISDN Digital Grade Loop/2W ISDN Digital Line Side Port - | † — | † | | | | | | | | | | | | | | |
| | UNE Zone 2 | | 2 | UEPPB | UEPPR | | 35.00 | | | | | | | | | | + |
| | 2W ISDN Digital Grade Loop/2W ISDN Digital Line Side Port - | ł | 3 | UEPPB | UEPPR | | 45.18 | | | | | 1 | 1 | | | | |
| | UNE Zone 3 2W ISDN Digital Grade Loop/2W ISDN Digital Line Skie Port - | + | <u>+ °</u> - | | 0001111 | | 10:10 | | | | | | | | | | |
| | UNE Zone 4 | | 4 | | | Ĺ | 67 61 | | | | | | | <u> </u> | | | |
| UNE | Loop Rates | | | | | | | | | | | | 15 75 | | | 1 97 | |
| | 2-Wire ISDN Digital Grade Loop - UNE Zone 1 | | 1 | UEPPB | UEPPR | USL2X | 18 26 | | | | | | 1 13 /3 | <u></u> | · | | + |
| _ | | | 2 | UEPPB | UEPPA | 1151.28 | 24 67 | | | | | | 15 75 | | 1 | 1 97 | · |
| | 2-Wire ISDN Digital Grade Loop - UNE Zone 2 | | 13 | UEPPB | UEPPR | | 34 85 | | | | | | 15 75 | | | 1 97 | |
| | 2-Wire ISDN Digital Grade Loop - UNE Zone 3 | + | | UEPPB | UEPPR | 1151.2X | 57.28 | | | | | | 15 75 | | | 1 97 | |
| | 2-Wire ISDN Digital Grade Loop - UNE Zone 4 | + | + | 102110 | | | | | | | | | 1 | | | | |
| UNE | Port Rate | + | + | LIEPPB | UEPPR | UEPPB | 10.33 | 190.80 | 133 22 | 100.72 | 21.13 | | 15.75 | | | 197 | |
| | Exchange Port - 2-Wire ISDN Line Side Port IRECURRING CHARGES - CURRENTLY COMBINED | + | + | | 021111 | | | | | | | | 1 | | | _ | _ |
| | 2-Wire ISDN Digital Grade Loop / 2-Wire ISDN Line Side Port | | | | | 1 | | · · · | | | | 1 | | | | | .1 |
| | Combination - Conversion | | | UEPPB | UEPPR | USACB | 0.00 | 38.73 | 27.17 | | | | 15.75 | | | 1 97 | |
| | DITIONAL NRCs | | | | | | | | | | | | | | | 1 | |
| | AL NUMBER PORTABILITY | 1 | 1 | | | | | | | | | | | . <u>+</u> | | <u>+</u> | - |
| | Local Number Portability (1 per port) | 1 | | UEPPB | UEPPR | LNPCX | 0 35 | 0.00 | 0.00 | | | | | | | | |
| | HANNEL USER PROFILE ACCESS: | | | | | | l | | | | ļ | | | | | | - |
| | CVS/CSD (DMS/5ESS) | | | UEPPB | | | 0.00 | 0.00 | | | | | | | | | |
| | CVS (EWSD) | | | UEPPB | UEPPR | U1UCB | 0.00 | 0.00 | | | | · | | | | | |
| | CSD | | | UEPPB | UEPPR | UIUCC | 0.00 | 0.00 | 0.00 | <u></u> | | | | + | | | |
| BC | HANNEL AREA PLUS USER PROFILE ACCESS: (AL,KY,LA,MS | SC,MS, | & TN) | | | <u> </u> | | | 0.00 | | | + | | | | | + |
| | CVS/CSD (DMS/5ESS) | | | UEPPB | UEPPR | UIUCD | 0.00 | 0.00 | | | | + | | + | | · · · ·· | |
| | CVS (EWSD) | | - | UEPPB | UEPPR | | 0.00 | 0.00 | | | | | | <u> </u> | | | 1 |
| | CSD | | | UEPPB | UEPPR | UIUCF | 0.00 | 0.00 | - 000 | <u>+</u> | | 1 | 1 | | | | |
| USF | ER TERMINAL PROFILE | | | | | 1011014 | 0.00 | 0.00 | 0.00 | <u> </u> | | | 1 | 1 | 1 | | |
| | User Terminal Profile (EWSD only) | | - | UEPPB | UEPPR | UIUMA | 0.00 | | 0.00 | | <u>†</u> | 1 | | | 1 | | |
| VEF | RTICAL FEATURES | _ | | 1.0000 | UCODO | UEPVF | 2.56 | 0.00 | 0 00 | | | 1 | 15.75 | | | 1 97 | / |
| | All Vertical Features - One per Channel B User Profile | | | UEPPB | UEPPH | UEPVF | 2.50 | 0.00 | | | 1 | | | | | | |
| INT | EROFFICE CHANNEL MILEAGE | | + | + | | + | | | | 1 | | 1 | | | | | |
| | Interoffice Channel mileage each, including first mile and | | | UEDDD | UEPPR | MIGNC | 22,5298 | 40 77 | 27.57 | 17.26 | 7.11 | 1 | 15 75 | | | 1.97 | / |
| | facilities termination | | | | UEPPR | | 0.0098 | 0.00 | | | 1 | | | | | | 1 |
| | Interoffice Channel mileage each, additional mile | | ÷ | UEFFD | 061111 | - Cartan | | | | | 1 | | | | | | |
| 4-W | VIRE DS1 DIGITAL LOOP WITH 4-WIRE ISDN DS1 DIGITAL TRUI | IN POR | <u>'</u> | | | | | | | | | | | | | | |
| | E Port/Loop Combination Rates 4W DS1 Digital Loop/4W ISDN DS1 Digital Trunk Port - UNE | | | 1 | | 1 | 1 | | 1 | 1 | | | | | | | 1 |
| | Zone 1 | | 11 | UEPPP | | <u> </u> | 155.43 | | <u> </u> | + | | | + | | 1 | | |
| | 4W DS1 Digital Loop/4W ISDN DS1 Digital Trunk Port - UNE | 1 | 2 | UEPPP | | | 205.74 | | | | | | | L | L | | |
| | Zone 2 4W DS1 Digital Loop/4W ISDN DS1 Digital Trunk Port - UNE | | + | UEFFF | | + | 200.74 | 1 | 1 | | | 1 | | 1 | | 1 | 1 |
| | Zone 3 | | 3 | UEPPP | | | 283 10 | | ļ | ļ | | | | · | | | + |
| | 4W DS1 Digital Loop/4W ISDN DS1 Digital Trunk Port - UNE | | | 1,0000 | | | 534.81 | | | ł | | | | | | t | |
| | Zone 4 | | 4 | UEPPP | | | 1 004.01 | | 1 | 1 | 1 | | | | | | |

| UNBU | NDLE | D NETWORK ELEMENTS - North Carolina | | | | | | | | | | | | Attachment: | 2 | Exhibit: B | |
|-------|----------|--|--------|----------|--------|--------|-------|----------|--------|-------------|------------|-----------|-----------|-------------|-------------|-------------|-------------|
| | | | | | | T | | | | 1 | | Svc Order | Svc Order | | | Incremental | Incrementa |
| | | | | 1 | ·-·· | 1 | | | | 1 | | Submitted | Submitted | | Charge - | Charge - | Charge - |
| | | | | 1 | | | | | | | 1 | Elec | Manually | Manual Svc | Manual Svc | Manual Svc | |
| CATEG | ORY | RATE ELEMENTS | Interi | Zone | BCS | USOC | | RA | ES(\$) | | | per LSR | per LSR | | | | |
| | •••• | | m | | | 1 | | | | i | 1 | perLSH | per LSH | Order vs. | Order vs. | Order vs. | Order vs. |
| | | | | | | | | | | 1 | 1 | | | Electronic- | Electronic- | Electronic- | Electronic- |
| | | | | | | | | | | | | | | 1st | Add'l | Disc 1st | Disc Add'l |
| | | | | | | | T T | Nonrec | urrino | Noorecurrin | Disconnect | | | 000 | Rates(\$) | | L |
| | | | | | | | Rec | First | Add'l | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| | | 2-Wire voice unbundled port with Caller + E484 ID - bus | | 1 | UEPBX | UEPBC | 2.28 | 90.00 | 90 00 | | | 0011120 | | 40 18 | 9.45 | JOWAN | SOMAN |
| | | 2-Wire voice unbundled port outgoing only - bus | | <u> </u> | UEPBX | UEPBO | 2.28 | 90.00 | 90 00 | | | | | 40.18 | 9.45 | | |
| | | 2-Wire voice unbundled incoming only port with Caller ID - Bus | | t | UEPBX | UPEB1 | 2.28 | 90.00 | 90.00 | | | | | 40.18 | 9.45 | | <u> </u> |
| | LOCAL | NUMBER PORTABILITY | | <u> </u> | 02.0/1 | 0. 201 | 2.20 | | 30.00 | | | | | 40.10 | 340 | | |
| | LUUNE | Local Number Portability (1 per port) | | <u> </u> | UEPBX | LNPCX | 0 35 | | | | | | | | | | |
| | FEATU | | | | | | | | | | | | | | | | L |
| | | All Features Offered | | <u> </u> | UEPBX | UEPVF | 3 40 | 0.00 | 0.00 | | | | | 40 18 | 9.45 | | |
| | | ECURRING CHARGES (NRCs) - CURRENTLY COMBINED | | | | | | 0.00 | | | | <u> </u> | | 40.10 | 9.45 | | |
| | | 2-Wire Voice Grade Loop / Line Port Combination - Conversion - | | <u> </u> | | | | | | | | · · · · · | | | | | |
| | | Switch-as-is | | | UEPBX | USAC2 | | 2.77 | 0 40 | | | | | 40 18 | 9 45 | | 1 |
| | | 2-Wire Voice Grade Loop / Line Port Combination - Conversion - | | <u> </u> | | 00ACE | | <u> </u> | | | | | | 40.10 | 945 | | |
| | | Switch with change | | | UEPBX | USACC | | 2 77 | 0 40 | | ł | | | 40 18 | 9.45 | | ŧ |
| | | 2-Wire Voice Grade Loop / Line Port Combination - Conversion - | | l | | 35700 | | ~ ~ / / | 040 | | | | | 40.18 | 9.45 | | f |
| | | Subsequent Database Update | | | | | | 1.42 | | | | | | 10 27 | | | 1 |
| | | ONAL NRCs | | | | | | 1.42 | | | | | | 10 27 | | | L |
| | | 2-Wire Voice Grade Loop/Line Port Combination - Subsequent | | | | | | | | | | | | | | | |
| | | | | ļ | UEPBX | USAS2 | | | 0.00 | | | | | | | | i i |
| | | Activity VOICE GRADE LOOP WITH 2-WIRE LINE PORT (RES - PBX) | | ┢ | UEFBA | USAGZ | | 0 00 | 0.00 | | | | | 40 18 | 9 45 | | |
| | | | | ļ | | | | | | | | | | | | | I |
| | UNE PO | ort/Loop Combination Rates | | l | | 1 | | | | | | | | | | | L |
| | | 2-Wire VG Loop/Port Combo - Statewide | | sw | | 1 | 16.46 | | | | | | | | | | |
| | UNELO | oop Rates | | l | | | | | | | | | | | | | |
| | | 2-Wire Voice Grade Loop (SL 1) - Statewide | | SW | UEPRG | UEPLX | 14.18 | | | | | | | | | | L |
| | | Voice Grade Line Port Rates (RES - PBX) | | L | | | | | | | | | | | | | |
| | ! | 2-Wire VG Unbundled Combination 2-Way PBX Trunk Port - | | 1 | | | | | | | | | | | | | l . |
| | | Res | | ļ | UEPRG | UEPRD | 2.28 | 90.00 | 90 00 | | | | | 40.18 | 9 45 | | |
| | LOCAL | | | ļ | | | | | | | | | | | | | |
| | | Local Number Portability (1 per port) | | · · · | UEPRG | LNPCP | 3.15 | 0.00 | 0.00 | | | | | | | | |
| | FEATU | | | | | | | | | | | | | | | | |
| | | All Features Offered | | | UEPRG | UEPVF | 3 40 | 0.00 | 0.00 | | | | | 40 18 | 9 45 | | |
| | | ECURRING CHARGES (NRCs) - CURRENTLY COMBINED | | | | | | | | | | | | | | | |
| | | 2-Wire Voice Grade Loop/ Line Port Combination (PBX) - | | | | | | | | | | | | | | | l . |
| | | Conversion - Switch-As-is | | <u> </u> | UEPRG | USAC2 | | 277 | 0.40 | | | | | 40.18 | 9.45 | | |
| | | 2-Wire Voice Grade Loop/ Line Port Combination (PBX) - | | | | | | | | | | | | | | | l . |
| | | Conversion - Switch with Change | | L | UEPRG | USACC | | 2 77 | 0.40 | | | | | 40 18 | 9 45 | | |
| | i | 2-Wire Voice Grade Loop / Line Port Combination - Conversion - | | 1 | | 1 | | | | | | | | | | | |
| | | Subsequent Database Update | | | | | | 1 42 | | | | | | 10 27 | | | |
| | ADDITI | IONAL NRCs | | | | | | | | | | | | | | | |
| | | 2-Wire Voice Grade Loop/ Line Port Combination (PBX) - | | 1 | | | | | | | | | | | | | |
| | | Subsequent Activity | | | UEPRG | USAS2 | 0.00 | 0 00 | 0.00 | | | | | 40.18 | 9.45 | | |
| - | | PBX Subsequent Activity - Change/Rearrange Multiline Hunt | |] | | 1 | | | | | | | | | | | |
| | 1 | Group | | | | | | 14.64 | 14.64 | | | | | 40.18 | 9.45 | | |
| | | E VOICE GRADE LOOP WITH 2-WIRE LINE PORT (BUS - PBX) | | | | | | | | | | | | | | | |
| | UNE PO | ort/Loop Combination Rates | | | | | | | | | | | | | | | |
| | | 2-Wire VG Loop/Port Combo - Statewide | | sw | | | 16.46 | | | | | | | | | | |
| | UNE LO | oop Rates | | | | | | | | | | | | | | | |
| | | 2-Wire Voice Grade Loop (SL 1) - Statewide | | ŚW | UEPPX | UEPLX | 14.18 | | | | | | | | | | |
| _ | 2-Wire | Voice Grade Line Port Rates (BUS - PBX) | | | | | | | | | | | | | | | |
| | | | | | | | 1 | | | | | | | | | | |
| | l I | Line Side Unbundled Combination 2-Way PBX Trunk Port - Bus | | | UEPPX | UEPPC | 2.28 | 90.00 | 90.00 | | | | | 40.18 | 9 45 | | |
| | | Line Side Unbundled Outward PBX Trunk Port - Bus | | | UEPPX | UEPPO | 2 28 | 90.00 | 90 00 | | | | | 40.18 | 9 45 | | |
| | | Line Side Unbundled Incoming PBX Trunk Port - Bus | | | UEPPX | UEPP1 | 2 28 | 90.00 | 90.00 | | | | | 40 18 | 9.45 | | |
| | <u> </u> | 2-Wire Voice Unbundled PBX LD Terminal Ports | | | UEPPX | UEPLD | 2 28 | 90.00 | 90 00 | | | | | 40.18 | 9.45 | | |
| I | | 2-Wire Voice Unbundled 2-Way Combination PBX Usage Port | | <u> </u> | UEPPX | UEPXA | 2 28 | 90.00 | 90 00 | | | | | 40 18 | 9 45 | | · |
| | | 2-Wire Voice Unbundled PBX Toll Terminal Hotel Ports | | | UEPPX | UEPXB | 2 28 | 90.00 | 90 00 | | | | | 40.18 | 9.45 | | |
| | <u> </u> | 2-Wire Voice Unbundled PBX LD DDD Terminals Port | | <u> </u> | UEPPX | UEPXC | 2.28 | 90 00 | 90.00 | | | | | 40.18 | 9.45 | | |
| | 1 | 2-Wire Voice Unbundled PBX LD Terminal Switchboard Port | | | UEPPX | UEPXD | 2.28 | 90.00 | 90 00 | | | | | 40 18 | 9 45 | | |
| | | 2-Wire Voice Unbundled PBX LD Terminal Switchboard IDD | | 1 | | | | | | | | | | | 545 | | |
| | | | | | | | | | | | | | | | | | |

.

| UNBUN | NDLED | NETWORK ELEMENTS - South Carolina | | | | | | | | | | | | Attachment: | 2 | Exhibit: B | |
|----------------------|--------|--|-------------|----------|----------------|----------------|--------|--------|------------------|--------------|---------------|-------|---|-------------|-----------|---|---|
| CATEGO | DRY | RATE ELEMENTS | interi m | Zone | BCS | USOC | | RAT | res(\$) | | | | Svc Order Submitted Manually per LSR | | | Incremental Charge - Manual Svc Order vs. Electronic- Disc 1st | Incrementat Charge - Manual Svc Order vs. Electronic- Disc Add'l |
| | | | | | | | Rec | Nonrec | | Nonrecurring | | | | | Rates(\$) | | <u> </u> |
| | | New York Combined Nature & Flowerty Controls As | | L | | | 160 | First | Add'l . | First | Add'l | SOMEC | SOMAN | SOMAN | SOMAN | SOMAN | SOMAN |
| | | Nonrecurring Currently Combined Network Elements Switch -As- Is Charge | | | UNCSX | UNCCC | | 561 | 5.61 | 7.00 | 7 00 | | 15.00 | | | | |
| | | ISON EXTENDED LOOP WITH DS1 INTEROFFICE TRANSPOR | TT (EEL | <u>+</u> | oncox | 0,1000 | | | 5.01 | 7.00 | /00 | | 15.69 | | | | ii |
| | | First 2-Wire ISDN Loop In a DS1 Interoffice Combination | | | | | | | | | | | | | | | |
| | | Transport - Zone 1 | | 1 | UNCNX | U1L2X | 25.21 | 117.58 | 80.03 | 53.05 | 10.61 | | 15 69 | | | | |
| | 1 | First 2-Wire ISDN Loop in a DS1 Interoffice Combination Transport - Zone 2 | | 2 | | U1L2X | 32 76 | 117.58 | 80 03 | 53.05 | 10 61 | | 15 69 | | | | |
| | | First 2-Wire ISDN Loop in a DS1 Interoffice Combination | | | 1.11.01.02 | | | | | | | | | | | | |
| | | Transport - Zone 3 Interoffice Transport - Dedicated - DS1 combination - Per Mile | | 3 | UNCNX UNC1X | U1L2X 1L5XX | 37.70 | 117.58 | 80.03 | 53 05 | 10.61 | | 15.69 | | | | |
| ├ ── † | | Interoffice Transport - Dedicated - DS1 combination - Fer Mile | | <u> </u> | 5.10 M | | 02/ | | | | | | | | | | |
| | - | Termination per month | | | UNC1X | UITFI | 61 71 | 89.47 | 81.99 | 16.39 | 14.48 | | 15 69 | | | | |
| | | Channelization · Channel System DS1 to DS0 combination - | | | | | | | | | | | | | | | |
| ┝──┼ | | per month | | | UNC1X | MQ1 | 107.57 | 91 24 | 62.71 | 10.56 | 981 | | 15 69 | | | | |
| | | 2-wire ISDN COCI (BRITE) - DS1 to DS0 Channel System combination - per month | | | UNCNX | UC1CA | 2.56 | 6.59 | 4.73 | | | | 15 69 | | | | |
| { | | Additional 2-wire ISDN Loop in same DS1Interoffice Transport Combination - Zone 1 | | 1 | UNCNX | U1L2X | 25.21 | 117 58 | 80.03 | 53.05 | 10.61 | | 15.69 | | | | |
| | | Additional 2-wire ISDN Loop in same DS1Interoffice Transport combination - Zone 2 | | | UNCNX | UIL2X | 32.76 | 117.58 | 80.03 | 53 05 | 10.61 | | 15.69 | | | | |
| | | Additional 2-wire ISDN Loop in same DS1Interoffice Transport combination - Zone 3 | | | UNCNX | U1L2X | 37.70 | 117.58 | 80.03 | 53.05 | 10.61 | | 15.69 | | | | |
| | | 2-wire ISDN COCI (BRITE) - DS1 to DS0 Channel System combination - per month | | | | UCICA | 2.56 | 6.59 | 4.73 | 53.05 | 1081 | | 15.69 | | | | |
| | | Nonrecurring Currently Combined Network Elements Switch -As- | | - | | | 2.30 | | | | | | | | | | |
| | Wibe | S Charge DS1 DIGITAL EXTENDED LOOP WITH DEDICATED STS-1 IN | TEROF | FICE T | UNC1X | UNCCC | | 5.61 | 5 61 | 7.00 | 7 00 | | 15.69 | | | | |
| ├── ſ | | First DS1 Loop in STS1 Interoffice Transport Combination - | | | | | | | | | | | | | | | |
| | | Zone 1 | | 1 | UNC1X | USLXX | 90.87 | 253 03 | 157.89 | 44.80 | 11.73 | | 15.69 | | | | |
| | | First DS1 Loop in STS1 Interoffice Transport Combination - Zone 2 | | 2 | UNC1X | USLXX | 155 43 | 253.03 | 157.69 | 44 80 | 11.73 | | 15.69 | | | | |
| | | First DS1 Loop In STS1 Interoffice Transport Combination - Zone 3 | | 3 | UNC1X | USLXX | 261 89 | 253 03 | 157.89 | 44.80 | 11.73 | | 15 69 | | | | |
| | | nteroffice Transport - Dedicated - STS1 combination - Per Mile Per Month | | | UNCSX | 1L5XX | 6.42 | | | | | | | | | | |
| 1 | | Interoffice Transport - Dedicated - STS1 combination - Facility | | | UNCSX | UITES | 704.44 | 279.37 | 163.12 | 60.33 | 58.59 | | 15.69 | | | 1 | |
| ├ ───┼ | | Termination STS1 to DS1 Channel System conbination per month | | | UNCSX | MQ3 | 144 02 | 178 54 | 94.18 | 33.33 | 31.90 | | 15.69 | | | | |
| ` <u></u> ⊢+ | | DS3 Interface Unit (D61 COCI) combination per month | | | UNC1X | UC1D1 | 8.64 | 6.59 | 4.73 | 11.00 | | | 15.69 | | | | |
| | | Additional DS1Loop in STS1 Interoffice Transport Combination - Zone 1 | | 1 | UNC1X | USLXX | 90.87 | 253.03 | 157.89 | 44.80 | 11 73 | | 15.69 | | | | |
| | | Additional DS1Loop in STS1 Interoffice Transport Combination - Zone 2 | | 2 | UNC1X | USLXX | 155.43 | 253.03 | 157.89 | 44.80 | 11 73 | | 15.69 | | | | |
| | | Additional DS1Loop in STS1 Interoffice Transport Combination - Zone 3 | | 3 | UNC1X | USLXX | 261.89 | 253.03 | 157.89 | 44.80 | 11.73 | | 15 69 | | | | |
| | | DS3 Interface Unit (DS1 COCI) combination per month | | | UNC1X | UC1D1 | 8.64 | 6.59 | 4.73 | | | | 15.69 | | | | |
| | I | Nonrecurring Currently Combined Network Elements Switch -As- Is Charge | | | UNCSX | UNCCC | | 5.61 | 5 61 | 7.00 | 7.00 | | 15.69 | | | | |
| | 4-WIRE | 56 KBPS DIGITAL EXTENDED LOOP WITH 56 KBPS INTERON | FFICET | RANS | PORT (EEL) | | | | | | | | | | | | |
| | - 10 | 4-wire 56 kbps Loop/4-wire 56 kbps Interoffice Transport Combination - Zone 1 | | 1 | UNCDX | UDL58 | 29.93 | 126.66 | 89.12 | 59.35 | 14.61 | | 15.69 | | | | |
| | | 4-wire 56 kbps Loop/4-wire 56 kbps Interoffice Transport Combination - Zone 2 | | 2 | UNCDX | UDL56 | 33.99 | 126.66 | 89.12 | 59.35 | 14. <u>61</u> | | 15.69 | | | | |
| | | 4-wire 56 kbps Loop/4-wire 56 kbps Interoffice Transport Combination - Zone 3 | | 3 | UNCDX | UDL56 | 34.74 | 126.66 | 89.12 | 59.35 | 14 61 | | 15.69 | | | | |
| | | Interoffice Transport - Dedicated - 4-wire 56 kbps combination - Per Mile | | | UNCDX | 1L5XX | 0.0134 | - | | | | | | | | | |
| | | Interoffice Transport - Dedicated - 4-wire 56 kbps combination - Facility Termination | | | UNCDX | U1TD5 | 13.41 | 40.63 | 27 47 | 16.77 | 6 91 | | 15 69 | | | | |

2.1.2 BellSouth will respond to a request for a Space Availability Report for a particular Premises within ten (10) calendar days of receipt of such request. BellSouth will make best efforts to respond in ten (10) calendar days to such a request when the request includes from two (2) to five (5) Premises within the same state. The response time for requests of more than five (5) Premises shall be negotiated between the Parties. If BellSouth cannot meet the ten (10) calendar day response time, BellSouth shall notify AmeriMex and inform AmeriMex of the time frame under which it can respond.

3. Collocation Options

- 3.1 <u>Cageless</u>. BellSouth shall allow AmeriMex to collocate AmeriMex 's equipment and facilities without requiring the construction of a cage or similar structure. BellSouth shall allow AmeriMex to have direct access to AmeriMex 's equipment and facilities. BellSouth shall make cageless collocation available in single bay increments. Except where AmeriMex 's equipment requires special technical considerations (e.g., special cable racking, isolated ground plane, etc.), BellSouth shall assign cageless Collocation Space in conventional equipment rack lineups where feasible. For equipment requiring special technical considerations, AmeriMex must provide the equipment layout, including spatial dimensions for such equipment pursuant to generic requirements contained in Telcordia GR-63-Core, and shall be responsible for compliance with all special technical requirements associated with such equipment.
- Caged. At AmeriMex's expense, AmeriMex may arrange with a Supplier certified by 3.2 BellSouth ("Certified Supplier") to construct a collocation arrangement enclosure in accordance with BellSouth's guidelines and specifications prior to starting equipment installation. BellSouth will provide guidelines and specifications upon request. Where local building codes require enclosure specifications more stringent than BellSouth's standard enclosure specification, AmeriMex and AmeriMex 's Certified Supplier must comply with the more stringent local building code requirements. AmeriMex 's Certified Supplier shall be responsible for filing and receiving any and all necessary permits and/or licenses for such construction. BellSouth shall cooperate with AmeriMex and provide, at AmeriMex's expense, the documentation, including existing building architectural drawings, enclosure drawings, and specifications required and necessary for AmeriMex to obtain the zoning, permits and/or other licenses. AmeriMex 's Certified Supplier shall bill AmeriMex directly for all work performed for AmeriMex pursuant to this Attachment and BellSouth shall have no liability for nor responsibility to pay such charges imposed by AmeriMex 's Certified Supplier. AmeriMex must provide the local BellSouth building contact with two Access Keys used to enter the locked enclosure. Except in case of emergency, BellSouth will not access AmeriMex 's locked enclosure prior to notifying AmeriMex . Upon request, BellSouth shall construct the enclosure for AmeriMex .
 - 3.2.1 BellSouth may elect to review AmeriMex 's plans and specifications prior to allowing construction to start to ensure compliance with BellSouth's guidelines and Version 1Q02: 02-20-02

- 5.10.1 Except in the case of the deployment of an advanced service which significantly degrades the performance of other advanced services or traditional voice band services, if AmeriMex fails to take curative action within 48 hours or if the violation is of a character which poses an immediate and substantial threat of damage to property, injury or death to any person, or any other significant degradation, interference or impairment of BellSouth's or any other entity's service, then and only in that event BellSouth may take such action as it deems appropriate to correct the violation, including without limitation the interruption of electrical power to AmeriMex 's equipment. BellSouth will endeavor, but is not required, to provide notice to AmeriMex prior to taking such action and shall have no liability to AmeriMex for any damages arising from such action, except to the extent that such action by BellSouth constitutes willful misconduct.
- 5.10.2 For purposes of this section, the term significantly degrade shall mean an action that noticeably impairs a service from a user's perspective. In the case of the deployment of an advanced service which significantly degrades the performance of other advanced services or traditional voice band services and AmeriMex fails to take curative action within 48 hours then BellSouth will establish before the relevant Commission that the technology deployment is causing the significant degradation. Any claims of network harm presented to AmeriMex or, if subsequently necessary, the relevant Commission must be supported with specific and verifiable information. Where BellSouth demonstrates that a deployed technology is significantly degrading the performance of other advanced services or traditional voice band services, AmeriMex shall discontinue deployment of that technology and migrate its customers to technologies that will not significantly degrade the performance of other such services. Where the only degraded service itself is a known disturber, and the newly deployed technology satisfies at least one of the criteria for a presumption that is acceptable for deployment under Section 47 C.F.R. 51.230, the degraded service shall not prevail against the newly-deployed technology.
- 5.11 <u>Personalty and its Removal</u>. Facilities and equipment placed by AmeriMex in the Remote Collocation Space shall not become a part of the Remote Site Location, even if nailed, screwed or otherwise fastened to the Remote Collocation Space but shall retain their status as personalty and may be removed by AmeriMex at any time. Any damage caused to the Remote Collocation Space by AmeriMex 's employees, agents or representatives shall be promptly repaired by AmeriMex at its expense.
- 5.12 <u>Alterations</u>. In no case shall AmeriMex or any person acting on behalf of AmeriMex make any rearrangement, modification, improvement, addition, or other alteration which could affect in any way space, power, HVAC, and/or safety considerations to the Remote Collocation Space or the BellSouth Remote Site Location without the written consent of BellSouth, which consent shall not be unreasonably withheld. The cost of any specialized alterations shall be paid by AmeriMex . Any such material

to enable AmeriMex to place a Firm Order. The Application Response will include, at a minimum, the configuration of the space, the Cable Installation Fee, Cable Records Fee, and the space preparation fees, as described in Section 8. When AmeriMex submits ten (10) or more applications within ten (10) calendar days, the initial fifteen (15) day response period will increase by ten (10) calendar days for every additional ten (10) applications or fraction thereof.

- 6.10.4 In Georgia and Mississippi, when space has been determined to be available, BellSouth will provide a written response ("Application Response") within twenty (20) calendar days of receipt of a Bona Fide application. The Application Response will include, at a minimum, the configuration of the space, the Cable Installation Fee, Cable Records Fee, and the space preparation fees, as described in Section 8.
- 6.10.5 In Louisiana, when space has been determined to be available, BellSouth will respond with a written response ("Application Response") within thirty (30) calendar days for one (1) to ten (10) applications; thirty (35) calendar days for eleven (11) to twenty (20) applications; and for requests of more than twenty (20) applications, it is increased by five (5) calendar days for every five (5) applications received within five (5) business days. The Application Response will include, at a minimum, the configuration of the space, the Cable Installation Fee, Cable Records Fee, and the space preparation fees, as described in Section 8.

6.11 Application Modifications.

6.11.1 If a modification or revision is made to any information in the Bona Fide application prior to Bona Fide Firm Order, with the exception of modifications to Customer Information, Contact Information or Billing Contact Information, either at the request of AmeriMex or necessitated by technical considerations, said application shall be considered a new application and shall be handled as a new application with respect to response and provisioning intervals and BellSouth will charge AmeriMex a full application fee as set forth in Exhibit C.

6.12 Bona Fide Firm Order.

6.12.1 Bona Fide Firm Order. In Alabama, Kentucky and North Carolina, AmeriMex shall indicate its intent to proceed with equipment installation in a BellSouth Remote Site Location by submitting a Physical Expanded Interconnection Firm Order document ("Firm Order") to BellSouth. A Firm Order shall be considered Bona Fide when AmeriMex Thas completed the Application/Inquiry process described in Section 6, preceding, and has submitted the Firm Order document indicating acceptance of the Application Response provided by BellSouth. The Bona Fide Firm Order must be received by BellSouth no later than five (5) business days after BellSouth's Application Response to AmeriMex 's Bona Fide application. The Bona Fide Firm Order must be received by BellSouth no later than thirty (30) calendar days after BellSouth's Application Response to AmeriMex 's Bona Fide application or the application will expire. If the BFFO is received between the fifth business day and the

thirtieth calendar day after the Application Response, then the intervals set forth in 7.1.1 will be extended day for day for each day after the fifth business day the Bona Fide Firm Order is received until the application expires.

- 6.12.2 Except as otherwise provided, in all States that have ordered provisioning intervals but not addressed Firm Order intervals, the following shall apply. AmeriMex shall indicate its intent to proceed with equipment installation in a BellSouth Remote Site Location by submitting a Firm Order to BellSouth. The Bona Fide Firm Order must be received by BellSouth no later than thirty (30) calendar days after BellSouth's Application Response to AmeriMex 's Bona Fide application or the application will expire.
- 6.12.3 BellSouth will establish a firm order date based upon the date BellSouth is in receipt of a Bona Fide Firm Order. BellSouth will acknowledge the receipt of AmeriMex 's Bona Fide Firm Order within seven (7) calendar days of receipt indicating that the Bona Fide Firm Order has been received. A BellSouth response to a Bona Fide Firm Order will include a Firm Order Confirmation containing the firm order date. No revisions will be made to a Bona Fide Firm Order.

7. <u>Construction and Provisioning</u>

7.1 Construction and Provisioning Intervals.

In Alabama, Kentucky and North Carolina, BellSouth will complete construction for 7.1.1collocation arrangements within seventy-six (76) business days from receipt of an application or as agreed to by the Parties. Under extraordinary conditions, BellSouth will complete construction for collocation arrangements within ninety-one (91) business days. Examples of extraordinary conditions include, but are not limited to, extended license or permitting intervals; major BellSouth equipment rearrangement or addition; power plant addition or upgrade; major mechanical addition or upgrade; major upgrade for ADA compliance; environmental hazard or hazardous materials abatement; and arrangements for which equipment shipping intervals are extraordinary in length. In the event AmeriMex submits a forecast as described in the following paragraph three (3) months or more prior to the application date, the above intervals shall apply. In the event AmeriMex submits such a forecast between two (2) months and three (3) months prior to the application date, the above intervals may be extended by one (1) additional month. In the event AmeriMex submits such a forecast less than two (2) months prior to the application date, the above intervals may be extended by sixty (60) calendar days. BellSouth will attempt to meet standard intervals for unforecasted requests and any interval adjustments will be discussed with AmeriMex at the time the application is received. Raw space, which is space lacking the necessary infrastructure to provide collocation space including but not limited to HVAC, Power, etc., conversion time frames fall outside the normal intervals and are negotiated on an individual case basis. Additionally, installations to existing collocation arrangements for line sharing or line splitting, which include adding cable, adding cable and splitter, and adding a splitter, will be forty five (45) business days from receipt of an application.

Reject Interval Distribution = $(e / f) \times 100$

- e = Service Requests Rejected in reported interval
- f = Total Number of Service Requests Rejected in Reporting Period

Report Structure

Fully Mechanized, Partially Mechanized, Total Mechanized, Non-Mechanized

- CLEC Specific
- CLEC Aggregate
- State, Region
- Fully Mechanized:
- 0 <= 4 minutes
- >4 <= 8 minutes
- >8 <= 12 minutes
- >12 <= 60 minutes
- $0 \le 1$ hour
- >1 <= 4 hours >4 - <= 8 hours
- >8 <= 12 hours
- >12 <= 16 hours
- >16 <= 20 hours
- >20 <= 24 hours
- > 24 hours
- Partially Mechanized:
- $0 \leq 1$ hour
- >1 <= 4 hours
- >4 <= 8 hours
- >8 <= 10 hours
- 0 <= 10 hours
- >10 <= 18 hours
- 0 <= 18 hours
- >18 <= 24 hours
- > 24 hours
- Non-Mechanized:
- 0 <= 1 hour
- >1 <= 4 hours
- >4 <= 8 hours
- >8 <= 12 hours >12 - <= 16 hours
- >16 <= 20 hours
- >20 <= 24 hours
- 0 <= 24 hours
- >24 hours
- · Average Interval in Days or Hours

Data Retained

| Relating to CLEC Experience | Relating to BellSouth Performance |
|-----------------------------|-----------------------------------|
| Report Month | Not Applicable |
| Reject Interval | |
| Total Number of LSRs | |
| Total number of Rejects | |
| State and Region | |

Section 6: Operator Services And Directory Assistance

OS-1: Speed to Answer Performance/Average Speed to Answer - Toll

Definition

Measurement of the average time in seconds calls wait before answered by a toll operator.

Exclusions

None

Business Rules

The clock starts when the customer enters the queue and the clock stops when a BellSouth representative answers the call or the customer abandons the call. The length of each call is determined by measuring, using a scanning technique, and accumulating the elapsed time from the entry of a customer call into the BellSouth call management system queue until the customer call is abandoned or transferred to BellSouth personnel assigned to handle calls for assistance. The system makes no distinction between CLEC customers and BellSouth customers.

Calculation

Speed to Answer Performance/Average Speed to Answer - Toll = a / b

- a = Total queue time
- b = Total calls answered

Note: Total queue time includes time that answered calls wait in queue as well as time abandoned calls wait in queue prior to abandonment.

Report Structure

- · Reported for the aggregate of BellSouth and CLECs
- State

Data Retained (on Aggregate Basis)

- For the items below, BellSouth's Performance Measurement Analysis Platform (PMAP) receives a final computation; therefore, no raw data file is available in PMAP
- Month
- Call Type (Toll)
- Average Speed of Answer

SQM Disaggregation - Analog/Benchmark

| SQM Level of Disaggregation | SQM Analog/Benchmark |
|-----------------------------|----------------------|
| None | Parity by Design |

SEEM Measure

| Γ | • | | SEEM Me | easure |
|---|----|---------|---------|--------|
| | No | Tier I | | |
| | | Tier II | | |

SEEM Disaggregation - Analog/Benchmark

| SEEM Disaggregation | SEEM Analog/Benchmark |
|---------------------|-----------------------|
| Not Applicable | Not Applicable |

ISDN

Integrated Services Digital Network

IPC

Interconnection Purchasing Center

L

LAN Local Area Network

LAUTO

The automatic processor in the LNP Gateway that validates LSRs and issues service orders.

LCSC

Local Carrier Service Center - The BellSouth center which is dedicated to handling CLEC LSRs, ASRs, and Preordering transactions along with associated expedite requests and escalations.

Legacy System

Term used to refer to BellSouth Operations Support Systems (see OSS)

LENS

Local Exchange Negotiation System - The BellSouth LAN/web server/OS application developed to provide both preordering and ordering electronic interface functions for CLECs.

LEO

Local Exchange Ordering - A BellSouth system which accepts the output of EDI, applies edit and formatting checks, and reformats the Local Service Requests in BellSouth Service Order format.

LERG

Local Exchange Routing Guide

LESOG

Local Exchange Service Order Generator - A BellSouth system which accepts the service order output of LEO and enters the Service Order into the Service Order Control System using terminal emulation technology.

LFACS

Loop Facilities Assessment and Control System

LIDB

Line Information Database

LISC

Local Interconnection Service Center - The center that issues trunk orders.

LMOS

Loop Maintenance Operations System - A BellSouth Operations System that stores the assignment and selected account information for use by downstream OSS and BellSouth personnel during provisioning and maintenance activities.

LMOS HOST LMOS host computer

LMOSupd LMOS updates

LMU Loop Make-up

LMUS